

Company name: Created by: Phone:

Date: 05/06/2018

Position | Qty. | Description

1 GT-C-250 PN8.6 G1 1/4 V



Note! Product picture may differ from actual product

Product No.: 96733308

Grundfos GT-C-250 PN8.6 G1 1/4 V is a Diaphragm pressure tank, with a capacity of 250,0 I and Vertical installation. The tanks are approved for drinking water. The GT-C-250 PN8.6 G1 1/4 V is designed for a maximum operation pressure of 8.6 bar and a maximum liquid temperature of 50 °C.

The tank is a lightweight composite pressure tank. The diaphragm is a chlorine-resistant 100 % butyl diaphragm with a precision-moulded copolymer polypropylene liner for superior air and water separation.

A pressure tank ensures controlled pressure in the water supply and thereby limits the switching frequency of the pump in case of low water consumption or leakage loss. The result is increased comfort in your installation by limiting the start/stop frequency of your pump, and it increases system comfort by compensating for pressure drops when a tap is opened, while reducing problems with water hammer in the pipework.

Liquid:

Maximum liquid temperature: 50 °C

Technical:

Membrane type: Diaphragm

Materials:

Material: Carbon steel



Company name: Created by: Phone:

Date: 05/06/2018

				Date:	05/06/2018	
Position	Otv	Description				
	αιy.					
		Installation:				
		Maximum operating pressure:	8.6 bar			
		Size:	250,0			
		0.20.	200,0			
		011				
		Others:				
		Net weight:	21.6 kg			
		Gross weight:	25 kg			
		Applicat. typ:	Standard			
		Application typ.	Otandara			
	I	l				