


Position	Qty.	Description
	1	<p>SB 3-35 A</p>  <p style="text-align: center;">Note! Product picture may differ from actual product</p> <p>Product No.: 97709345</p> <p>The SB pump is a submersible booster pump for the pumping of clean water. It is especially suitable for rainwater applications. The pump is available in two main versions:</p> <ul style="list-style-type: none"> • with integrated suction strainer (1 mm mesh) • with side inlet which includes a flexible suction hose with floating suction strainer (1 mm mesh). <p>In both versions, the pump is available with or without float switch. The float switch can be used for automatic operation or dry-running protection of the pump.</p> <p>Liquid:</p> <p>Pumped liquid: Water Liquid temperature range: 0 .. 40 °C Liquid temperature during operation: 20 °C Density: 998.2 kg/m³</p> <p>Technical:</p> <p>Rated flow: 2.76 m³/h Rated head: 25.2 m Impeller nom: 102 mm Type of impeller: CLOSED Maximum particle size: 1 mm Approvals and markings: 2 Curve tolerance: ISO9906:2012 3B</p> <p>Materials:</p> <p>Pump housing: PP30GF Impeller: PPO20GF</p> <p>Installation:</p> <p>Maximum ambient temperature: 50 °C Pump outlet: G 1" Maximum installation depth: 10 m Type of suction: STRAINER</p> <p>Electrical data:</p> <p>Rated power - P2: 0.54 kW Mains frequency: 50 Hz Rated voltage: 1 x 220-240 V Rated current: 3.8 A Starting current: 12 A</p>



Company name:

Created by:

Phone:

Date:

20/06/2018

Position	Qty.	Description
		<p>Cos phi: 0.94 Rated speed: 2800 rpm Capacitor size - run: 13 μF/450 V Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 15 m Cable type: H07RN-F 3G1 Type of cable plug: AUS</p> <p>Others: Net weight: 9.42 kg Gross weight: 10 kg Shipping volume: 0.022 m³</p>