

## Product Specification

# Low Angle Wobbler

### Applications:

Above ground sprinkler installation for all row crops and mining heap leach processes.

### Description:

- Senninger Wobbler has a unique off-centre rotary action
- The design provides extremely uniform coverage over a large diameter at low pressures.



### Specifications:

- One moving part – longer life
- Made from high impact engineering grade thermoplastics.
- Inlet 20mm BSP Male (15mm option also)
- Flow rates 5 LPM – 52.2 LPM
- Angle of trajectory 12°

Low Angle Wobbler	Nozzle Pressure (Kpa)			
	75	100	150	200
<b>#6 Nozzle - Gold (2.38mm)</b> Flow (L/s) Diameter at 46cm riser	0.05 9.00	0.06 9.70	0.07 10.7	0.08 11.0
<b>#7 Nozzle - Lime (2.78mm)</b> Flow (L/s) Diameter at 46cm riser	0.07 9.40	0.08 10.0	0.10 11.0	0.12 11.3
<b>#8 Nozzle - Lavender (3.18mm)</b> Flow (L/s) Diameter at 46cm riser	0.09 9.90	0.11 10.3	0.13 11.2	0.15 11.6
<b>#9 Nozzle - Grey (3.57mm)</b> Flow (L/s) Diameter at 46cm riser	0.12 10.2	0.14 10.6	0.17 11.5	0.20 11.8
<b>#10 Nozzle - Turquoise (3.97mm) **</b> Flow (L/s) Diameter at 46cm riser	0.15 10.5	0.17 10.9	0.21 11.7	0.24 12.1
<b>#11 Nozzle - Yellow (4.37mm)</b> Flow (L/s) Diameter at 46cm riser	0.18 10.5	0.20 11.1	0.25 12.0	0.29 12.4
<b>#12 Nozzle - Red (4.76mm)</b> Flow (L/s) Diameter at 46cm riser	0.21 10.6	0.24 11.3	0.30 12.3	0.34 12.8
<b>#13 Nozzle - White (5.16mm)</b> Flow (L/s) Diameter at 46cm riser	0.25 10.9	0.28 11.6	0.35 12.6	0.40 13.1
<b>#14 Nozzle - Blue (5.56mm)</b> Flow (L/s) Diameter at 46cm riser	0.28 11.1	0.32 11.8	0.40 12.9	0.46 13.4
<b>#15 Nozzle - Dark Brown (5.95mm)</b> Flow (L/s) Diameter at 46cm riser	0.33 11.4	0.38 12.1	0.46 13.1	0.53 13.5
<b>#16 Nozzle - Orange (6.35mm)</b> Flow (L/s) Diameter at 46cm riser	0.37 11.7	0.42 12.3	0.52 13.2	0.60 13.7
<b>#17 Nozzle - Dark Green (6.75mm)</b> Flow (L/s) Diameter at 46cm riser	0.41 12.0	0.47 12.5	0.58 13.4	0.67 13.8
<b>#18 Nozzle - Purple (7.14mm)</b> Flow (L/s) Diameter at 46cm riser	0.46 12.3	0.53 12.8	0.65 13.5	0.75 14.0
DIAMETERS ARE SHOWN IN METERS. Maximum stream height is 76cm above nozzle using 3.97mm (#10) nozzle at 150 Kpa.				

### E-MAIL

hrproducts@bigpond.com

### WEB SITE

www.hrproducts.com.au

### PERTH

207 BANNISTER ROAD  
CANNING VALE  
WESTERN AUSTRALIA 6155  
PHONE: (08) 9455 1677  
TOLL FREE: 1 800 998 037

### ADELAIDE

Cnr WILSON ST & FREDERICK RD  
ROYAL PARK  
SOUTH AUSTRALIA 5014  
PHONE: (08) 8341 0008  
TOLL FREE: 1 800 888 125

### BRISBANE

14-16 TOLMER PLACE  
SPRINGWOOD  
QUEENSLAND 4127  
PHONE: (07) 3290 1200  
TOLL FREE: 1 800 777 325

### SYDNEY

11-13 SAMMUT STREET  
SMITHFIELD  
NSW 2164  
PHONE: (02) 9725 5733  
TOLL FREE: 1 800 251 945

### MELBOURNE

Cnr Waterdale Rd & Vernon Ave  
HEIDELBERG HEIGHTS  
VICTORIA 3081  
PHONE: (03) 9457 7500  
TOLL FREE: 1 800 331 168

### MACKAY

MOBILE: 0418 742 144

### COBRAM

MOBILE: 0417 054 475

### NEWCASTLE

MOBILE: 0418 292 769

### DUBBO

MOBILE: 0409 489 092