


| Position | Qty. | Description |
|----------|------|---|
| | 1 | <p>Unilift KP 150 AV 1</p>  <p style="text-align: center;">Note! Product picture may differ from actual product</p> <p>Product No.: 011K4500 Submersible drainage pump</p> <p>Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 1-phase canned motor in insulation class F with thermal overload protection.</p> <p>The pump is fitted with suction strainer and a carrying handle and is supplied with a 5 m mains cable and vertical level switch for automatic start and stop.</p> <p>The impeller is a semi-open impeller for 10 mm free passage suitable for pumping groundwater, surface water, rain water and similar liquids.</p> <p>The pump has a double shaft seal consisting of two lip seals with grease in-between.</p> <p>The pump has an outer casing ensuring continuous cooling of the motor by the pumped liquid. The rotor shaft operates in two maintenance-free carbon bearings cooled by the pumped liquid</p> <p>The motor is filled with a non-toxic motor liquid.</p> <p>Liquid: Pumped liquid: Any Newtonian liquid Liquid temperature range: 0 .. 50 °C Density: 998.2 kg/m³</p> <p>Technical: Maximum particle size: 10 mm</p> <p>Materials: Pump housing: Stainless steel DIN W.-Nr. 1.4301 AISI 304 Impeller: Stainless steel DIN W.-Nr. 1.4031 AISI 304</p> <p>Installation:</p> |



Company name:

Created by:

Phone:

Date:

02/02/2018

| Position | Qty. | Description |
|----------|------|--|
| | | Pump outlet: Rp 1 1/4 Maximum installation depth: 2 m |
| | | Electrical data: Power input - P1: 300 W Mains frequency: 50 Hz Rated voltage: 1 x 230-240 V Rated current: 1.3 A Capacitor size - run: 8 µF/400 V Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 5 m Type of cable plug: AU |
| | | Others: Net weight: 6.5 kg Gross weight: 7 kg Shipping volume: 0.013 m ³ |

011K4500 Unilift KP 150 AV 1 50 Hz

