


Position	Qty.	Description												
	1	<p data-bbox="320 338 528 365">Unilift KP 250 M 1</p> <div data-bbox="435 405 592 752" style="text-align: center;">  </div> <p data-bbox="711 770 1193 797" style="text-align: center;">Note! Product picture may differ from actual product</p> <p data-bbox="320 801 632 862">Product No.: 012K4100 Submersible drainage pump</p> <p data-bbox="320 891 847 1037">Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 1-phase canned motor in insulation class F with thermal overload protection.</p> <p data-bbox="320 1070 791 1155">The pump is fitted with a suction strainer, a carrying handle and is supplied with a 5 m mains cable.</p> <p data-bbox="320 1189 847 1274">The impeller is a semi-open impeller for 10 mm free passage suitable for pumping groundwater, surface water, rain water and similar liquids.</p> <p data-bbox="320 1308 839 1368">The pump has a double shaft seal consisting of two lip seals with grease in-between.</p> <p data-bbox="320 1402 887 1514">The pump has an outer casing ensuring continuous cooling of the motor by the pumped liquid. The rotor shaft operates in two maintenance-free carbon bearings cooled by the pumped liquid</p> <p data-bbox="320 1547 839 1574">The motor is filled with a non-toxic motor liquid.</p> <p data-bbox="320 1608 408 1635">Liquid:</p> <table data-bbox="320 1637 919 1727"> <tr> <td>Pumped liquid:</td> <td>Any Newtonian liquid</td> </tr> <tr> <td>Liquid temperature range:</td> <td>0 .. 50 °C</td> </tr> <tr> <td>Density:</td> <td>998.2 kg/m³</td> </tr> </table> <p data-bbox="320 1760 448 1787">Technical:</p> <table data-bbox="320 1789 759 1816"> <tr> <td>Maximum particle size:</td> <td>10 mm</td> </tr> </table> <p data-bbox="320 1850 440 1877">Materials:</p> <table data-bbox="320 1879 887 2051"> <tr> <td>Pump housing:</td> <td>Stainless steel DIN W.-Nr. 1.4301 AISI 304</td> </tr> <tr> <td>Impeller:</td> <td>Stainless steel DIN W.-Nr. 1.4031 AISI 304</td> </tr> </table> <p data-bbox="320 2085 456 2112">Installation:</p>	Pumped liquid:	Any Newtonian liquid	Liquid temperature range:	0 .. 50 °C	Density:	998.2 kg/m ³	Maximum particle size:	10 mm	Pump housing:	Stainless steel DIN W.-Nr. 1.4301 AISI 304	Impeller:	Stainless steel DIN W.-Nr. 1.4031 AISI 304
Pumped liquid:	Any Newtonian liquid													
Liquid temperature range:	0 .. 50 °C													
Density:	998.2 kg/m ³													
Maximum particle size:	10 mm													
Pump housing:	Stainless steel DIN W.-Nr. 1.4301 AISI 304													
Impeller:	Stainless steel DIN W.-Nr. 1.4031 AISI 304													



Company name:

Created by:

Phone:

Date: 02/02/2018

Position	Qty.	Description
		Pump outlet: Rp 1 1/4 Maximum installation depth: 2 m
		Electrical data: Power input - P1: 480 W Mains frequency: 50 Hz Rated voltage: 1 x 230-240 V Rated current: 2.2 A Capacitor size - run: 8 µF/400 V Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 5 m Type of cable plug: AU
		Others: Net weight: 6.5 kg Gross weight: 7 kg Shipping volume: 0.013 m ³

012K4100 Unilift KP 250 M 1 50 Hz

