


Position	Qty.	Description
	1	<p data-bbox="320 338 526 367">Unilift KP 350 A 1</p> <div data-bbox="435 409 592 752" style="text-align: center;">  </div> <p data-bbox="711 770 1193 797" style="text-align: center;">Note! Product picture may differ from actual product</p> <p data-bbox="320 801 632 862">Product No.: 013N4700 Submersible drainage pump</p> <p data-bbox="320 891 847 1037">Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 1-phase canned motor in insulation class F with thermal overload protection.</p> <p data-bbox="320 1070 839 1187">The pump is fitted with suction strainer and a carrying handle and is supplied with a 5 m mains cable and float switch for automatic start and stop.</p> <p data-bbox="320 1220 847 1305">The impeller is a semi-open impeller for 10 mm free passage suitable for pumping groundwater, surface water, rain water and similar liquids.</p> <p data-bbox="320 1339 839 1400">The pump has a double shaft seal consisting of two lip seals with grease in-between.</p> <p data-bbox="320 1433 887 1550">The pump has an outer casing ensuring continuous cooling of the motor by the pumped liquid. The rotor shaft operates in two maintenance-free carbon bearings cooled by the pumped liquid.</p> <p data-bbox="320 1583 839 1610">The motor is filled with a non-toxic motor liquid.</p> <p data-bbox="320 1644 919 1760">Liquid: Pumped liquid: Any Newtonian liquid Liquid temperature range: 0 .. 50 °C Density: 998.2 kg/m³</p> <p data-bbox="320 1794 759 1854">Technical: Maximum particle size: 10 mm</p> <p data-bbox="320 1888 887 2083">Materials: Pump housing: Stainless steel DIN W.-Nr. 1.4301 AISI 304 Impeller: Stainless steel DIN W.-Nr. 1.4031 AISI 304</p>

Position	Qty.	Description
		<p>Installation:</p> <p>Pump outlet: Rp 1 1/4</p> <p>Maximum installation depth: 2 m</p> <p>Electrical data:</p> <p>Power input - P1: 700 W</p> <p>Mains frequency: 50 Hz</p> <p>Rated voltage: 1 x 220-240 V</p> <p>Rated current: 3.2 A</p> <p>Capacitor size - run: 10 µF/400 V</p> <p>Enclosure class (IEC 34-5): IP68</p> <p>Insulation class (IEC 85): F</p> <p>Length of cable: 5 m</p> <p>Type of cable plug: AU</p> <p>Others:</p> <p>Net weight: 7.3 kg</p> <p>Gross weight: 7.7 kg</p> <p>Shipping volume: 0.013 m³</p>

013N4700 Unilift KP 350 A 1 50 Hz

