


Position	Qty.	Description
	1	<p>Unilift AP12.40.04.3</p>  <p style="text-align: right;">Note! Product picture may differ from actual product</p> <p>Product No.: 96011024 Submersible drainage pump type</p> <p>Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 3-phase totally enclosed motor in insulation class F. The pump is fitted with a suction strainer.</p> <p>The impeller is a SEMI OPEN impeller for 12 mm free passage suitable for pumping groundwater, surface water, rain water and similar.</p> <p>The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.</p> <p>The pump has a riser pipe, a cooling jacket for continuous cooling of the motor by the pumped liquid and long-life deep-groove greased-for-life ball bearings.</p> <p>The pump is ready for use as it is fitted with carrying handle and is supplied with a 10 m mains cable. The mains cable is of the plug type with glass sealing compound in the socket to prevent penetration of humidity into the stator windings.</p> <p>Liquid: Pumped liquid: Any Newtonian liquid Liquid temperature range: 0 .. 55 °C Density: 998.2 kg/m³</p> <p>Technical: Type of impeller: SEMI OPEN Maximum particle size: 12 mm</p> <p>Materials: Pump housing: Stainless steel DIN W.-Nr. 1.4301 AISI 304 Impeller: Stainless steel</p>

Position	Qty.	Description
		<p>DIN W.-Nr. 1.4301 AISI 304</p> <p>Installation: Pump outlet: Rp 1 1/2 Maximum installation depth: 7 m</p> <p>Electrical data: Power input - P1: 0.7 kW Mains frequency: 50 Hz Rated voltage: 3 x 400 V Rated current: 1.2 A Cos phi - power factor: 0,83 Rated speed: 2800 rpm Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 10 m Type of cable plug: NONE</p> <p>Others: Net weight: 10 kg Gross weight: 11 kg</p>

96011024 Unilift AP12.40.04.3 50 Hz

