


Position	Qty.	Description
	1	<p><b>UPS 25-60 130</b></p>  <p style="text-align: center;"><b>Note! Product picture may differ from actual product</b></p> <p>Product No.: <a href="#">96281476</a></p> <p>The pump is of the canned rotor type, i.e. pump and motor form an integral unit without shaft seal and with only two gaskets for sealing. The bearings are lubricated by the pumped liquid. The pump has 3-step speed selector. The pump is characterized by:</p> <ul style="list-style-type: none"> <li>* Ceramic shaft and radial bearings.</li> <li>* Carbon axial bearing.</li> <li>* Stainless steel rotor can and bearing plate.</li> <li>* Corrosion-resistant impeller, Composite, PES/PP.</li> <li>* Cast iron pump housing.</li> </ul> <p>The motor is a 1-phase motor. No additional motor protection is required.</p> <p><b>Liquid:</b></p> <p>Pumped liquid: Water  Liquid temperature range: 2 .. 110 °C  Liquid temperature during operation: 60 °C  Density: 983.2 kg/m<sup>3</sup></p> <p><b>Technical:</b></p> <p>TF class: 110  Approvals on nameplate: VDE,EAC</p> <p><b>Materials:</b></p> <p>Pump housing: Cast iron  EN-JL1030  ASTM 30 B</p> <p>Impeller: Composite, PES/PP</p> <p><b>Installation:</b></p> <p>Amb. max at 80 dgr C liquid: 40 °C  Maximum operating pressure: 10 bar  Pipe connection: G 1 1/2  Pressure rating: PN 10  Port-to-port length: 130 mm</p> <p><b>Electrical data:</b></p> <p>Power input in speed 1: 50 W  Power input in speed 2: 60 W  Max. power input: 70 W  Mains frequency: 50 Hz</p>



Company name:

Created by:

Phone:

Date:

06/02/2018

Position	Qty.	Description
		Rated voltage: 1 x 230 V Current in speed 1: 0.22 A Current in speed 2: 0.27 A Current in speed 3: 0.3 A Capacitor size - run: 2.5 $\mu$ F Enclosure class (IEC 34-5): IP44 Insulation class (IEC 85): F  <b>Others:</b> Net weight: 2.4 kg Gross weight: 2.6 kg Shipping volume: 0.004 m <sup>3</sup>

## 96281476 UPS 25-60 130 50 Hz

