


Position	Qty.	Description
	1	<p><b>UNILIFT CC5 - A1</b></p>  <p>Note! Product picture may differ from actual product</p> <p>Product No.: <a href="#">96280972</a></p> <p>Grundfos Unilift CC pumps are single-stage submersible pumps with a low suction ability down to 3 mm water level.</p> <p>The pumps are designed for pumping rainwater and grey wastewater, e.g. from</p> <ul style="list-style-type: none"> <li>• washing machines, baths, sinks, etc. from low-lying parts of buildings up to sewer level</li> <li>• cellars or buildings prone to flooding</li> <li>• draining wells</li> <li>• wells for surface water with inlets from roof gutters, pits, tunnels, etc.</li> <li>• swimming pools, ponds or fountains.</li> </ul> <p>The pumps are suitable for both stationary and portable use. They are for automatic operation. The pumps allow free passage of particles up to <math>\varnothing 10</math> mm.</p> <p>The motor incorporates automatic overload protection cutting out the motor in case of overload. When cooled to normal temperature, the motor restarts automatically.</p> <p><b>Technical:</b> Maximum particle size: 10 mm</p> <p><b>Materials:</b> Pump housing: PP 15 GF Impeller: PPOm 20 GF</p> <p><b>Installation:</b> Pump outlet: 1.1/4" Maximum installation depth: 10 m</p> <p><b>Liquid:</b> Pumped liquid: Any Newtonian liquid Liquid temperature range: 0 .. 40 °C Density: 998.2 kg/m<sup>3</sup></p> <p><b>Electrical data:</b> Mains frequency: 50 Hz Rated voltage: 1 x 220-240 V</p>

Position	Qty.	Description
		<p>Rated current: 0.98 A</p> <p>Capacitor size - run: 4 µF/450 V</p> <p>Enclosure class (IEC 34-5): IP68</p> <p>Insulation class (IEC 85): B</p> <p>Length of cable: 5 m</p> <p>Type of cable plug: AUS</p> <p><b>Others:</b></p> <p>Net weight: 4.51 kg</p> <p>Gross weight: 5.27 kg</p> <p>Shipping volume: 0.017 m<sup>3</sup></p>

## 96280972 UNILIFT CC5 - A1 50 Hz

