



**GENERAL INFO**

**MAXIPLUS™ STAINLESS STEEL HOUSINGS**

The Puretec SS MaxiPlus™ are ideal for large scale commercial and industrial applications.

The Puretec SS MaxiPlus™ Series housings are suitable for the most demanding applications such as high pressure, temperature or corrosive, harsh conditions. The housings are capable of temperatures up to 99°C at 2,070 kPa and a maximum flow of 180 litres per minute.

**HOUSING SPECIFICATIONS**

- Material of Construction: 304 stainless steel
- Connection: BSP thread
- Filter Cartridge: 10" or 20" x 4.5"  
Double open end cartridges not included
- O-Ring: Buna-N
- Maximum Temperature: 99°C
- Maximum Pressure: 2,070 kPa
- Application: Suitable for industry and other relative water treatment

**FEATURES & BENEFITS**

- Large diameter for high flow rates.
- High pressure and temperature applications.
- Suitable for harsh and corrosive conditions.
- Polished 304 stainless steel construction.
- Heavy duty units for large scale commercial/industrial applications.

**PERFORMANCE DATA**

Model	Description	Housing Size (inches)	Connection Size	Max. Flow (Lpm)
<b>SS25MP1</b>	304 Stainless steel head and housing	10"	1"	90
<b>SS40MP2</b>	304 Stainless steel head and housing	20"	1½"	180

Note: Each housing includes a spanner tool, a mounting bracket kit and drain plug. For warm or hot water applications, we strongly recommend to test the chloride level in the water source & confirm suitability with the Puretec team.