



GENERAL INFO

SEDIMENT REMOVAL CARTRIDGE

Melt Blown / Dual Graded Sediment Cartridges

The Puretec MB Series cartridges can be used with many liquids and are very effective for sediment, rust, sand, silt and algae removal. These cartridges do not impart taste, odour or colour to the liquid being filtered. The polypropylene construction provides superior chemical resistance and is not prone to bacterial attack.

The MB Series graded density filter design means that the filter is more dense towards the center of the filter. This increased depth ensures extremely high sediment reduction efficiencies and longer cartridge life.

FEATURES & BENEFITS

- Graded depth filtration.
- Protects appliances and health with sediment-free water
- Temperature ratings up to 60 °C.
- Flow rates up to 178 litres/minute.

CARTRIDGE SPECIFICATIONS

Size	Ordering Code	Micron Rating	Size	Flow (Lpm)
10"	MB951	0.5	Standard 2.5" X 10"	23
	MB011	1	Standard 2.5" X 10"	25
	MB051	5	Standard 2.5" X 10"	26
	MB101	10	Standard 2.5" X 10"	30
	MB201	20	Standard 2.5" X 10"	32
	MB501	50	Standard 2.5" X 10"	34
20"	MB012	1	Standard 2.5" X 20"	46
	MB052	5	Standard 2.5" X 20"	52
	MB102	10	Standard 2.5" X 20"	60
	MB202	20	Standard 2.5" X 20"	64
	MB502	50	Standard 2.5" X 20"	68
10" LD	MB01LD1	1	Large diameter 4.5" X 10"	73
	MB05LD1	5	Large diameter 4.5" X 10"	74
	MB10LD1	10	Large diameter 4.5" X 10"	78
	MB20LD1	20	Large diameter 4.5" X 10"	82
	MB50LD1	50	Large diameter 4.5" X 10"	88
20" LD	MB01LD2	1	Large diameter 4.5" X 20"	150
	MB05LD2	5	Large diameter 4.5" X 20"	154
	MB10LD2	10	Large diameter 4.5" X 20"	158
	MB20LD2	20	Large diameter 4.5" X 20"	162
	MB50LD2	50	Large diameter 4.5" X 20"	178

Micron rating is nominal. Protect from freezing.