Molded Case Circuit Breakers

Panelboard Mounting Circuit Breakers

Selection

Special Application Breakers

Switching Neutrals¹

evitoring (vocation)				
Breaker	Ampere			
Туре	Rating	Catalog Number		
BG	15	BG215∎		
2-Wire	20	BG220■		
Common Trip	30	BG230■		
BG	15	BG315∎		
3-Wire	20	BG320∎		
Common Trip	30	BG330■		

HID Lighting[®]

For high-intensity discharge lamp loads having in-rush currents above the instantaneous trip setting of a standard breaker.

D.	15	B115HID ^② ■
BL 1-Pole	20	B120HID ^②
1-Pole	30	B130HID∎
BL 2-Pole	15	B215HID ^② ■
	20	B220HID ^②
	30	B230HID■

Tungsten Lighting

For high wattage, tungsten-lamp loads in-rush currents above the instantaneous trip setting of a standard breaker.

BL 1-Pole	15	B115T ²
	20	B120T ²

Molded Case Switch

For applications that do not require overcurrent protection.

BL	30	B230S
2-Pole	60	B260S



[■] Built to order. Allow 2–3 weeks for delivery.

① HACR rated.

[©] UL Listed for frequent switching applications (SWD). 120V AC fluorescent lighting.