



Powering Business Worldwide

pe.eaton.com

Eaton Series C complete molded case circuit breaker

FDC2050L

UPC:786679325506

Dimensions:

- Height: 6 IN
- Length: 3.38 IN
- Width: 2.75 IN

Weight:2 LB

Warranties: No Data

Specifications:

- Amperage Rating: 50A
- Interrupt Rating: 200 kAIC at 240 Vac, 100 kAIC at 480 Vac
- Number Of Poles: Two-pole
- Voltage Rating: 600 Vac, 250 Vdc
- Trip Type: Fixed thermal, fixed magnetic
- Circuit Breaker Type: FDC
- Circuit Breaker Frame Type: Complete breaker
- Series: Series C
- Terminals: Line and load
- Frame: F-frame
- Frequency Rating: 50/60 Hz

Supporting documents:

- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)
- [Application of Tap Rules to Molded Case Breaker Terminals](#)
- [UL listed 100%-rated molded case circuit breakers](#)
- [Plug-in adapters for molded case circuit breakers product aid](#)
- [Power metering and monitoring with Modbus](#)



RTU product aid

- MOEM MCCB Product Selection Guide
- StrandAble terminals product aid
- Current limiting Series C molded case circuit breakers product aid
- Motor protection circuit breakers product aid
- Circuit breaker motor operators product aid
- Multi-wire lugs product aid
- Molded case circuit breakers
- Eatons Volume 4-Circuit Protection
- Time Current Curves for Series C® F-Frame Circuit Breakers
- FDC2 AutoCAD 2D Footprint (mm)
- FDC2 3D Inventor
- FDC2 2D PDF
- FDC2 3D Model Xchange
- Installation Instructions for EHD, EDB, EDS, ED, EDH, EDC, FDB, FD, HFD, FDC, HFDDC Circuit Breakers and Molded Case Switches
- Breaker service centers
- Counterfeit and Gray Market Awareness Guide
- Series C J-Frame molded case circuit breakers time current curves
- MOEM MCCB product selection guide
- Eaton Specification Sheet - FDC2050L
- Series C F-Frame molded case circuit breakers
- Series C G-Frame molded case circuit breakers time current curves

Certifications:

- UL Listed

Product compliance: No Data