



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Eaton Series C complete molded case circuit breaker

**GHC1090**

**UPC:**786679174050

### Dimensions:

- **Height:** 4.88 IN
- **Length:** 2.63 IN
- **Width:** 1IN

**Weight:**.6 LB

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Amperage Rating:** 90A
- **Interrupt Rating:** 14 kAIC at 277 Vac
- **Number Of Poles:** Single-pole
- **Voltage Rating:** 277 Vac, 125 Vdc
- **Trip Type:** Fixed thermal, fixed magnetic
- **Circuit Breaker Type:** GHC
- **Circuit Breaker Frame Type:** Complete breaker
- **Frame Size:** G-frame
- **Series:** Series C
- **Frequency Rating:** 50/60 Hz

### Supporting documents:

- [UL listed 100%-rated molded case circuit breakers](#)
- [Application of Tap Rules to Molded Case Breaker Terminals](#)
- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)
- [MOEM MCCB Product Selection Guide](#)



- [Power metering and monitoring with Modbus RTU product aid](#)
- [Current limiting Series C molded case circuit breakers product aid](#)
- [Circuit breaker motor operators product aid](#)
- [Plug-in adapters for molded case circuit breakers product aid](#)
- [Multi-wire lugs product aid](#)
- [Motor protection circuit breakers product aid](#)
- [StrandAble terminals product aid](#)
- [Molded case circuit breakers](#)
- [Eatons Volume 4-Circuit Protection](#)
- [G-frame Molded Case Circuit Breaker Drawing](#)
- [Series C GC/GHC Circuit Breaker - IL](#)
- [Series C GB/GHB/GDB Circuit Breakers - IL](#)
- [Breaker service centers](#)
- [Series C G-Frame Time Current Curves](#)
- [Series C J-Frame molded case circuit breakers time current curves](#)
- [Series C G-Frame molded case circuit breakers time current curves](#)
- [MOEM MCCB product selection guide](#)
- [Series C F-Frame molded case circuit breakers](#)
- [Type GHB/GHC/GD/GPS 2 and 3-pole, 15-100A Time Curve](#)

**Certifications:**

- [UL Listed](#)

**Product compliance:** No Data