H361DS

Safety switch, heavy duty, fusible, 30A, 3 poles, 20 hp, 20 hp, 600 VAC/DC, NEMA 4, 4X, 5, 304 steel





Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device Application	Heavy application
Disconnect Type	Fusible disconnect
Factory Installed Neutral	None
Phase	3 phase
Number of Poles	3
Current Rating	30 A
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 4/4X/5 stainless steel 304
Maximum Horse Power Rating	5 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 15 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 7.5 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 20 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 5 Hp 250 V at DC 15 hp 600 V at DC

Complementary

Short Circuit Current Rating	10 KA H or K
· ·	200 kA R or J
Fuse type	H or K
	R or J
Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	3-wire (3P)
Wire Size	AWG 12AWG 6 aluminium
	AWG 14AWG 6 copper
Tightening torque	45 Lbf.In (5.08 N.m) 0.02 in ² (13.3 mm ²) (AWG 6)
	40 Lbf.In (4.52 N.m) 0.01 in ² (8.367 mm ²) (AWG 8)
	35 lbf.in (3.95 N.m) 0.000.01 in ² (2.065.261 mm ²) (AWG 14AWG 10)
Depth	5.11 in (129.79 mm)
Width	8.67 in (220.22 mm)
Height	14.93 in (379.22 mm)
Net Weight	13.23 lb(US) (6 kg)

Environment

Certifications	UL listed file E2875

Ordering and shipping details

00010-H&HU SW,2&3P,N4,SS,30-200A	
DE1	
785901023616	
1	
13.74 lb(US) (6.232 kg)	
	DE1 785901023616 1

Returnability	Yes
Country of origin	US
Packing Units	
Unit Type of Package 1	PCE
Package 1 Height	5.80 in (14.732 cm)
Package 1 width	9.10 in (23.114 cm)
Package 1 Length	17.50 in (44.45 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	70
Package 2 Weight	961.00 lb(US) (435.902 kg)
Package 2 Height	45.00 in (114.3 cm)
Package 2 width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	€Yes

Contractual warranty

China RoHS Regulation

Environmental Disclosure

PVC free

Warranty	18 months

Yes

Product Environmental Profile

Approximate Dimensions

