H364NRB

Safety switch, heavy duty, fusible, 200A, 3 poles, 150 hp, 600 VAC/DC, NEMA 3R, bolt-on hub, neutral factory installed





Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device application	Heavy application
Disconnect Type	Fusible disconnect
Factory Installed Neutral	Neutral (factory installed)
Phase	3 phase
Number of Poles	3
Current Rating	200 A
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 3R galvannealed steel
Maximum Horse Power Rating	50 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 125 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 60 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 150 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 40 Hp 250 V at DC 50 hp 600 V at DC

Complementary

Short Circuit Current Rating	10 KA H or K
	200 kA R or J
Fuse type	H or K
	R or J
Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	4-wire (3PH + N)
Wire Size	AWG 6250 kcmil copper or aluminium
Tightening torque	275 lbf.in (31.07 N.m) 0.020.20 in² (13.3127 mm²) (AWG 6250 kcmil)
Depth	8.5 in (215.90 mm)
Width	18.63 in (473.20 mm)
Height	29.25 in (742.95 mm)
Net Weight	56.50 lb(US) (25.63 kg)

Environment

Certifications	UL listed file E2875

Ordering and shipping details

Category	00009-H&HU SW,2&3P,N3R,30-200A
Discount Schedule	DE1
GTIN	785901616313
Nbr. of units in pkg.	1
Package weight(Lbs)	46.25 lb(US) (20.979 kg)
Returnability	Yes
Country of origin	US

Packing Units

5		
Unit Type of Package 1	PCE	
Package 1 Height	8.30 in (21.082 cm)	
Package 1 width	19.30 in (49.022 cm)	
Package 1 Length	30.90 in (78.486 cm)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	15	
Package 2 Weight	723.00 lb(US) (327.947 kg)	
Package 2 Height	46.00 in (116.84 cm)	
Package 2 width	40.00 in (101.6 cm)	
Package 2 Length	48.00 in (121.92 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes

Contractual warranty

Warranty 18 months	- Contraction training	
	•	18 months