

Typical F-Frame Breaker  
F-Frame Breaker with Electronic Trip Unit



## F-Frame (10–225 Amperes)

### Product Description

- All Eaton's F-Frame circuit breakers are HACR rated
- All circuit breakers 10 through 30 amperes are suitable for HID (high intensity discharge) use
- All F-Frame circuit breakers are suitable for reverse feed use

## Contents

### Description

	<i>Page</i>
Product Overview . . . . .	<b>V4-T2-220</b>
Standards and Certifications . . . . .	<b>V4-T2-221</b>
Quick Reference . . . . .	<b>V4-T2-222</b>
G-Frame (15–100 Amperes) . . . . .	<b>V4-T2-225</b>
F-Frame (10–225 Amperes)	
Catalog Number Selection . . . . .	<b>V4-T2-240</b>
Product Selection . . . . .	<b>V4-T2-242</b>
Accessories . . . . .	<b>V4-T2-253</b>
Technical Data and Specifications . . . . .	<b>V4-T2-254</b>
Dimensions and Weights . . . . .	<b>V4-T2-256</b>
J-Frame (70–250 Amperes) . . . . .	<b>V4-T2-257</b>
K-Frame (70–400 Amperes) . . . . .	<b>V4-T2-265</b>
L-Frame (125–600 Amperes) . . . . .	<b>V4-T2-289</b>
M-Frame (300–800 Amperes) . . . . .	<b>V4-T2-315</b>
N-Frame (400–1200 Amperes) . . . . .	<b>V4-T2-326</b>
R-Frame (800–2500 Amperes) . . . . .	<b>V4-T2-341</b>
Motor Circuit Protectors (MCP) . . . . .	<b>V4-T2-360</b>
Motor Protection Circuit Breakers (MPCB) . . . . .	<b>V4-T2-371</b>
Type ELC Current Limiter Attachment (Size 0–4) . . . . .	<b>V4-T2-373</b>
Current Limiting Circuit Breaker Module . . . . .	<b>V4-T2-374</b>
Internal Accessories . . . . .	<b>V4-T2-377</b>
External Accessories . . . . .	<b>V4-T2-410</b>

# 2.4

## Molded Case Circuit Breakers



### Series C

#### Catalog Number Selection

This information is presented only as an aid to understanding catalog numbers. It is not to be used to build catalog numbers for circuit breakers or trip units.

2

#### FD-Frame Circuit Breakers with Thermal-Magnetic Trip Unit Technology



**Type HFD Thermal-Magnetic Circuit Breakers with Non-Interchangeable Trip Units  
(Includes Terminals on Load End Only)**

Maximum Continuous Ampere Rating at 40 °C	277 Vac Maximum, 125 Vdc 65 kAIC at 277 Vac	600 Vac Maximum, 250 Vdc 65 kAIC at 480 Vac		
	Single-Pole Catalog Number	Two-Pole Catalog Number	Three-Pole Catalog Number	Four-Pole Catalog Number
15	HFD1015 <sup>①</sup>	HFD2015	HFD3015	HFD4015
20	HFD1020 <sup>①</sup>	HFD2020	HFD3020	HFD4020
25	HFD1025	HFD2025	HFD3025	HFD4025
30	HFD1030	HFD2030	HFD3030	HFD4030
35	HFD1035	HFD2035	HFD3035	HFD4035
40	HFD1040	HFD2040	HFD3040	HFD4040
45	HFD1045	HFD2045	HFD3045	HFD4045
50	HFD1050	HFD2050	HFD3050	HFD4050
60	HFD1060	HFD2060	HFD3060	HFD4060
70	HFD1070	HFD2070	HFD3070	HFD4070
80	HFD1080	HFD2080	HFD3080	HFD4080
90	HFD1090	HFD2090	HFD3090	HFD4090
100	HFD1100	HFD2100	HFD3100	HFD4100
110	HFD1110	HFD2110	HFD3110	HFD4110
125	HFD1125	HFD2125	HFD3125	HFD4125
150	HFD1150	HFD2150	HFD3150	HFD4150
175	—	HFD2175	HFD3175	HFD4175
200	—	HFD2200	HFD3200	HFD4200
225	—	HFD2225	HFD3225	HFD4225

**Note**

<sup>①</sup> UL listed for SWD applications, see NEC Article 240.83(d).