



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Eaton Series C molded case circuit breaker frame

**HLD2600F**

**UPC:**786679138007

### Dimensions:

- **Height:** 8.25 IN
- **Length:** 8.25 IN
- **Width:** 8.25 IN

**Weight:**15 LB

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Type:** Frame only
- **Amperage Rating:** 600A
- **Interrupt Rating:** 100 kAIC at 240 Vac, 65 kAIC at 480 Vac
- **Number Of Poles:** Two-pole
- **Voltage Rating:** 600 Vac, 250 Vdc
- **Trip Type:** Fixed thermal, fixed magnetic
- **Circuit Breaker Type:** HLD
- **Frame Size:** L-frame
- **Series:** Series C
- **Frequency Rating:** 50-60 Hz

### Supporting documents:

- [UL listed 100%-rated molded case circuit breakers](#)
- [Application of Tap Rules to Molded Case Breaker Terminals](#)
- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)
- [Power metering and monitoring with Modbus](#)



RTU product aid

- [MOEM MCCB Product Selection Guide](#)
- [Motor protection circuit breakers product aid](#)
- [Current limiting Series C molded case circuit breakers product aid](#)
- [Circuit breaker motor operators product aid](#)
- [StrandAble terminals product aid](#)
- [Plug-in adapters for molded case circuit breakers product aid](#)
- [Multi-wire lugs product aid](#)
- [Eatons Volume 4-Circuit Protection](#)
- [Molded case circuit breakers](#)
- [Time Current Curves for Series C® F-Frame Circuit Breakers](#)
- [Series C L-Frame with Digitrip OPTIM Trip Unit - IL](#)
- [Installation Instructions for EHD, EDB, EDS, ED, EDH, EDC, FDB, FD, HFD, FDC, HFDDC Circuit Breakers and Molded Case Switches](#)
- [Shunt Trip for Series C L-Frame - IL](#)
- [Breaker service centers](#)
- [Counterfeit and Gray Market Awareness Guide](#)
- [Eaton Specification Sheet - HLD2600F](#)
- [MOEM MCCB product selection guide](#)
- [Series C F-Frame molded case circuit breakers](#)
- [Series C J-Frame molded case circuit breakers time current curves](#)
- [Series C G-Frame molded case circuit breakers time current curves](#)
- [Series C L-Frame 125-600A, 240-600V Time Current Curves](#)

**Certifications:**

- [UL Listed](#)

**Product compliance:** No Data