



Powering Business Worldwide

pe.eaton.com

Eaton Series C molded case circuit breaker frame

JDC3250F

UPC:786679516393

Dimensions:

- **Height:** 4.13 IN
- **Length:** 4.06 IN
- **Width:** 4.13 IN

Weight:9.15 LB

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Frame only
- **Amperage Rating:** 250A
- **Interrupt Rating:** 200 kAIC at 240 Vac, 100 kAIC at 480 Vac
- **Number Of Poles:** Three-pole
- **Voltage Rating:** 600 Vac, 250 Vdc
- **Trip Type:** Fixed thermal, fixed magnetic
- **Circuit Breaker Type:** JDC
- **Frame Size:** J-frame
- **Series:** Series C
- **Frequency Rating:** 50-60 Hz

Supporting documents:

- [UL listed 100%-rated molded case circuit breakers](#)
- [Application of Tap Rules to Molded Case Breaker Terminals](#)
- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)
- [MOEM MCCB Product Selection Guide](#)



- [Motor protection circuit breakers product aid](#)
- [Power metering and monitoring with Modbus RTU product aid](#)
- [StrandAble terminals product aid](#)
- [Plug-in adapters for molded case circuit breakers product aid](#)
- [Circuit breaker motor operators product aid](#)
- [Current limiting Series C molded case circuit breakers product aid](#)
- [Multi-wire lugs product aid](#)
- [Molded case circuit breakers](#)
- [Eaton's Volume 4-Circuit Protection](#)
- [J-frame Molded Case Circuit Breaker Drawing](#)
- [Breaker service centers](#)
- [MOEM MCCB product selection guide](#)
- [Series C F-Frame molded case circuit breakers](#)
- [Series C, J-frame Time Current Curve](#)
- [Series C G-Frame molded case circuit breakers time current curves](#)
- [Series C J-Frame molded case circuit breakers time current curves](#)
- [Cutler-Hammer Series C Time-Current Curves for J-Frame Circuit Breakers](#)

Certifications:

- UL Listed

Product compliance: No Data