Product data sheet Characteristics

LA36175 3P 175A 600V, LA FA/LA MOLDED CASE CIRCUIT BREAKER



Main

Product or Component Type	Circuit breaker	
Trip Unit Technology	Thermal-magnetic	

Complementary

Line Rated Current	175 A	
Number of Poles	3P	
Breaking capacity code	A	
Mounting Mode	I-Line	
Wiring Configuration	3-wire	
Magnetic Hold Current	875 A	
Magnetic Tripping Current	1750 A	
Electrical connection	Lugs load I-Line connection line	
Terminal identifier	AL400LA	
Height	11 in (279.40 mm)	
Width	6 in (152.40 mm)	
Depth	5.84 in (148.34 mm)	

Environment

	and the second s
Certifications	CSA
	UL Listed

Ordering and shipping details

Category	01040-LA/LH BRKR, SW, MAG-GARD
Discount Schedule	DE2
GTIN	00785901339281
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	Yes
Country of origin	MX

Offer Sustainability

Contractual warranty

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

18 months