



# Circuit breaker, LA, LH, Q4, I-Line, 400A, 3 pole, 22 kA at 600VAC, phase ABC

LA36400

N	1	а	ı	r

Product or component type	Circuit breaker
Trip Unit Technology	Thermal-magnetic

# Complementary

Complementary		
[In] rated current	400 A	
Number of Poles	3P	
Breaking capacity code	A	
Mounting Mode	I-Line	
Wiring Configuration	3-wire	
Magnetic Hold Current	2000 A	
Magnetic Tripping Current	4000 A	
Electrical connection	Lugs load I-Line connection line	
Terminal identifier	AL400LA	
Tightening torque	115.06 lbf.in (13 N.m) 0.070.47 in² (42304 mm²) AWG 1600 kcmil) 115.06 lbf.in (13 N.m) 0.070.20 in² (42127 mm²) AWG 1250 kcmil)	
Phase connection	ABC	
Height	11 in (279.40 mm)	
Width	6 in (152.40 mm)	
Depth	5.84 in (148.34 mm)	
Circuit breaker application	HACR rated	

### **Environment**

Certifications	UL listed	
	CSA	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.00 in (22.86 cm)
Package 1 Width	11.70 in (29.718 cm)

Package 1 Length	17.50 in (44.45 cm)	
Package 1 Weight	18.34 lb(US) (8.32 kg)	
Offer Sustainability		
Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	

Product Environmental Profile

Halogen free plastic parts product

Yes

## Recommended replacement(s)

Halogen content performance

**Environmental Disclosure** 

**PVC** free