



Powering Business Worldwide

pe.eaton.com

Eaton Series C complete molded case circuit breaker

LDC3600

UPC:786679033715

Dimensions:

- **Height:** 8.25 IN
- **Length:** 8.25 IN
- **Width:** 8.25 IN

Weight:21 LB

Warranties: No Data

Specifications:

- **Amperage Rating:** 600A
- **Interrupt Rating:** 200 kAIC at 240 Vac, 100 kAIC at 480 Vac
- **Number Of Poles:** Three-pole
- **Voltage Rating:** 600 Vac, 250 Vdc
- **Trip Type:** Fixed thermal, fixed magnetic
- **Circuit Breaker Type:** LDC
- **Circuit Breaker Frame Type:** Complete breaker
- **Series:** Series C
- **Terminals:** Line and load
- **Frame:** L-frame
- **Frequency Rating:** 50-60 Hz
- **Terminal Material:** Aluminum

Supporting documents:

- [UL listed 100%-rated molded case circuit breakers](#)
- [Application of Tap Rules to Molded Case Breaker Terminals](#)
- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)
- [Motor protection circuit breakers product aid](#)
- [Plug-in adapters for molded case circuit](#)



- breakers product aid
- StrandAble terminals product aid
- Circuit breaker motor operators product aid
- Current limiting Series C molded case circuit breakers product aid
- MOEM MCCB Product Selection Guide
- Multi-wire lugs product aid
- Power metering and monitoring with Modbus RTU product aid
- Eatons Volume 4-Circuit Protection
- Molded case circuit breakers
- LD-frame Molded Case Circuit Breaker Drawing
- Shunt Trip for Series C L-Frame - IL
- Breaker service centers
- Series C G-Frame molded case circuit breakers time current curves
- Series C J-Frame molded case circuit breakers time current curves
- Series C F-Frame molded case circuit breakers
- Eaton Specification Sheet - LDC3600
- MOEM MCCB product selection guide
- Series C L-Frame 125-600A, 240-600V Time Current Curves

Certifications:

- UL 489

Product compliance: No Data