



Main

Product or component type	Circuit breaker
Range of product	I-Line
Trip Unit Type	Thermal-magnetic
Rating Code	H

Complementary

Line Rated Current	225 A
Number of Poles	3P
Interrupt Rating	65 kA at 240 V AC 35 kA at 480 V AC 25 kA at 600 V AC 50 kA at 250 V DC 35 kA at 480Y/277 V AC 20 kA at 500 V DC 25 kA at 600Y/347 V AC
System Voltage	250 V DC 500 V DC 600 V AC
Mounting mode	I-Line
Electrical connection	I-Line connection line Lugs load
Wire Gauge	AWG 1...600 kcmil (aluminium/copper) 1 cable(s) AWG 1...250 kcmil (aluminium/copper) 2 cable(s)
Terminal Type	AL400LA
Magnetic hold current	1125 A
Magnetic tripping current	2250 A
Height	12.5 in
Width	6 in
Depth	4 in

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Product certifications	CSA UL listed
------------------------	------------------

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1304 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations
