



Powering Business Worldwide

pe.eaton.com

Eaton Series C complete molded case circuit breaker

MDL3600

UPC:782114585986

Dimensions:

- **Height:** 10.75 IN
- **Length:** 10.75 IN
- **Width:** 10.75 IN

Weight:30 LB

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Amperage Rating:** 600A
- **Interrupt Rating:** 65 kAIC at 240 Vac, 50 kAIC at 480 Vac
- **Number Of Poles:** Three-pole
- **Voltage Rating:** 600 Vac, 250 Vdc
- **Trip Type:** Fixed thermal, fixed magnetic
- **Circuit Breaker Type:** MDL
- **Circuit Breaker Frame Type:** Complete breaker
- **Frame Size:** M-frame
- **Series:** Series C
- **Frame:** MDL-frame
- **Frequency Rating:** 50-60 Hz

Supporting documents:

- [UL listed 100%-rated molded case circuit breakers](#)
- [Application of Tap Rules to Molded Case Breaker Terminals](#)
- [Application of Multi-Wire Terminals for Molded](#)



Case Circuit Breakers

- [Current limiting Series C molded case circuit breakers product aid](#)
- [Power metering and monitoring with Modbus RTU product aid](#)
- [Plug-in adapters for molded case circuit breakers product aid](#)
- [Multi-wire lugs product aid](#)
- [Motor protection circuit breakers product aid](#)
- [StrandAble terminals product aid](#)
- [Circuit breaker motor operators product aid](#)
- [MOEM MCCB Product Selection Guide](#)
- [Eatons Volume 4-Circuit Protection](#)
- [Molded case circuit breakers](#)
- [MDL-frame Molded Case Circuit Breaker Drawing](#)
- [Installation Instructions for Motor Operator for L-Frame and MDL-Frame Circuit Breakers and Molded Case Switches](#)
- [Breaker service centers](#)
- [Series C J-Frame molded case circuit breakers time current curves](#)
- [Series C G-Frame molded case circuit breakers time current curves](#)
- [MOEM MCCB product selection guide](#)
- [Series C F-Frame molded case circuit breakers](#)
- [Molded Case Circuit Breaker Application On Grounded B-Phase Systems](#)
- [Series C MDL-Frame 400-800A, 240-600V Time Current Curves](#)

Certifications:

- [UL Listed](#)

Product compliance: No Data