Product data sheet Characteristics

Q4L3250

Circuit breaker, LA, LH, Q4 molded case, unit mount, thermal-magnetic, 250A, 3 pole, 25kA, 240VAC





Main		
Product or Component Type	Circuit breaker	
Trip Unit Technology	Thermal-magnetic	

Complementary

Line Rated Current	250 A
Number of Poles	3P
Breaking capacity code	Q4
Mounting Mode	Unit mount
Magnetic Hold Current	1250 A
Magnetic Tripping Current	2500 A
Electrical connection	Lugs load Lugs line
Terminal identifier	AL400LA
Tightening torque	371.73 Lbf.ln (42 N.m) 0.080.47 in² (50300 mm²) (AWG 1600 kcmil) 371.73 lbf.in (42 N.m) 0.080.19 in² (50120 mm²) (AWG 1250 kcmil)
Height	11 in (279.40 mm)
Width	6 in (152.40 mm)
Depth	5.84 in (148.34 mm)

Environment

CSA
CSA IEC
UL Listed

Ordering and shipping details

Category	00933-Q4L BREAKER & SWITCH
Discount Schedule	DE2
GTIN	785901649250
Nbr. of units in pkg.	1
Package weight(Lbs)	16.31 lb(US) (7.4 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	9.09 in (23.1 cm)
Package 1 width	11.61 in (29.5 cm)
Package 1 Length	17.28 in (43.9 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	[☑] China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Contractual warranty		
Warranty	18 months	