# Product data sheet Characteristics

## Q4L3350

Circuit breaker, LA, LH, Q4 molded case, unit mount, thermal-magnetic, 350A, 3 pole, 25kA, 240VAC





Main		
Product or Component Type	Circuit breaker	
Trip Unit Technology	Thermal-magnetic	

Complementary

Complementary	
Line Rated Current	350 A
Number of Poles	3P
Breaking capacity code	Q4
Mounting Mode	Unit mount
Magnetic Hold Current	1750 A
Magnetic Tripping Current	3500 A
Electrical connection	Lugs load Lugs line
Terminal identifier	AL400LA
Tightening torque	371.73 Lbf.ln (42 N.m) 0.080.47 in² (50300 mm²) (AWG 1600 kcmil) 371.73 lbf.in (42 N.m) 0.080.19 in² (50120 mm²) (AWG 1250 kcmil)
Height	11 in (279.40 mm)
Width	6 in (152.40 mm)
Depth	5.84 in (148.34 mm)

#### Environment

JL Listed
EC
CSA
E

#### Ordering and shipping details

Category	00933-Q4L BREAKER & SWITCH	
Discount Schedule	DE2	
GTIN	785901649274	
Nbr. of units in pkg.	1	
Package weight(Lbs)	16.07 lb(US) (7.29 kg)	
Returnability	Yes	
Country of origin	MX	

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	9.20 in (23.368 cm)
Package 1 width	11.30 in (28.702 cm)
Package 1 Length	17.70 in (44.958 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

#### Contractual warranty

Contractual warranty		
Warranty	18 months	