

QUICKLAG Type QC Single-Pole



Contents

| <i>Description</i> | <i>Page</i> |
|--|-----------------|
| Quick Reference | V4-T1-2 |
| QUICKLAG Plug-On Types HQP, QPHW, QHPX, QHPW | V4-T1-5 |
| QUICKLAG Plug-On Ground Fault and Equipment Protectors, Types QPGFT, QPHGFT, QPGFEP, QPHGFEP | V4-T1-8 |
| Bolt-On Types BAB, QBHW, HBAX, HBAW | V4-T1-11 |
| Bolt-On Arc Fault Circuit Interrupter Types QBAF, QBCAF | V4-T1-14 |
| Bolt-On Ground Fault and Equipment Protectors, Types QBGFT, QBHGFT, QBGFEP, QBHGFEP | V4-T1-16 |
| Cable-In/Cable-Out Types QC, QCD, QCHW, QHCX, QHCW | V4-T1-20 |
| Product Selection | V4-T1-22 |
| Dimensions | V4-T1-23 |
| Cable-In/Cable-Out, 1/2-Inch Wide, Types QCR, QCF, QCRH, QCFH | V4-T1-23 |
| Cable-In/Cable-Out Ground Fault and Equipment Protectors, Types QCGFT, QCHGFT, QCGFEP, QCHGFEP | V4-T1-27 |
| Solenoid-Operated, Remote-Controlled Latching Types BABRP, BABRSP, BRRP and CLRP | V4-T1-30 |
| Solenoid Operator—Remote Controlled Latching for Type GHBS, GBHS and GHQRSP Breakers | V4-T1-33 |
| International Rated Types HQP, BA, QC, GFMB, GFXBC | V4-T1-36 |
| Special Application Breakers, Types HQP, BA, QC | V4-T1-39 |

Cable-In/Cable-Out Types QC, QCD, QCHW, QHCX, QHCW

Product Description

- All products 10–100A are HACR rated
- Switching duty rated for 120 Vac fluorescent light applications only

Standards and Certifications

- Built and listed to UL 489
- All products UL and CSA listed



QUICKLAG Type: QCHW 22,000A Interrupting Capacity Thermal-Magnetic Breakers

| Continuous Ampere Rating at 40°C | Single-Pole 120/240 Vac Catalog Number | Two-Pole 120/240 Vac Catalog Number | Two-Pole 240 Vac Catalog Number | Three-Pole 240 Vac Catalog Number | Four-Pole 240 Vac Catalog Number |
|----------------------------------|--|---|---------------------------------------|---|--|
| 15 | QCHW1015 ① | QCHW2015 | QCHW2015H | QCHW3015H | QCHW4015H |
| 20 | QCHW1020 ① | QCHW2020 | QCHW2020H | QCHW3020H | QCHW4020H |
| 25 | QCHW1025 | QCHW2025 | QCHW2025H | QCHW3025H | QCHW4025H |
| 30 | QCHW1030 | QCHW2030 | QCHW2030H | QCHW3030H | QCHW4030H |
| 35 | QCHW1035 | QCHW2035 | QCHW2035H | QCHW3035H | QCHW4035H |
| 40 | QCHW1040 | QCHW2040 | QCHW2040H | QCHW3040H | QCHW4040H |
| 45 | QCHW1045 | QCHW2045 | QCHW2045H | QCHW3045H | QCHW4045H |
| 50 | QCHW1050 | QCHW2050 | QCHW2050H | QCHW3050H | QCHW4050H |
| 55 | QCHW1055 | QCHW2055 | QCHW2055H | QCHW3055H | QCHW4055H |
| 60 | QCHW1060 | QCHW2060 | QCHW2060H | QCHW3060H | QCHW4060H |
| 70 | QCHW1070 | QCHW2070 | QCHW2070H | QCHW3070H | QCHW4070H |
| 70 | — | QCHW2080 | QCHW2080H | QCHW3080H | QCHW4080H |
| 90 | — | QCHW2090 | QCHW2090H | QCHW3090H | QCHW4090H |
| 100 | — | QCHW2100 | QCHW2100H | QCHW3100H | QCHW4100H |

QUICKLAG Type: QHCX 42,000A Interrupting Capacity Thermal-Magnetic Breakers

| Continuous Ampere Rating at 40°C | Single-Pole 120/240 Vac Catalog Number | Two-Pole 120/240 Vac Catalog Number | Two-Pole 240 Vac Catalog Number | Three-Pole 240 Vac Catalog Number | Four-Pole 240 Vac Catalog Number |
|----------------------------------|--|---|---------------------------------------|---|--|
| 15 | QHCX1015 ① | QHCX2015 | — | QHCX3015H | — |
| 20 | QHCX1020 ① | QHCX2020 | — | QHCX3020H | — |
| 25 | QHCX1025 | QHCX2025 | — | QHCX3025H | — |
| 30 | QHCX1030 | QHCX2030 | — | QHCX3030H | — |
| 35 | QHCX1035 | QHCX2035 | — | QHCX3035H | — |
| 40 | QHCX1040 | QHCX2040 | — | QHCX3040H | — |
| 45 | QHCX1045 | QHCX2045 | — | QHCX3045H | — |
| 50 | QHCX1050 | QHCX2050 | — | QHCX3050H | — |
| 55 | QHCX1055 | QHCX2055 | — | QHCX3055H | — |
| 60 | QHCX1060 | QHCX2060 | — | QHCX3060H | — |
| 70 | QHCX1070 | QHCX2070 | — | QHCX3070H | — |
| 70 | — | QHCX2080 | — | QHCX3080H | — |
| 90 | — | QHCX2090 | — | QHCX3090H | — |
| 100 | — | QHCX2100 | — | QHCX3100H | — |

QUICKLAG Type: QHCW 65,000A Interrupting Capacity Thermal-Magnetic Breakers

| Continuous Ampere Rating at 40°C | Single-Pole 120/240 Vac Catalog Number | Two-Pole 120/240 Vac Catalog Number | Two-Pole 240 Vac Catalog Number | Three-Pole 240 Vac Catalog Number | Four-Pole 240 Vac Catalog Number |
|----------------------------------|--|---|---------------------------------------|---|--|
| 15 | QHCW1015 ① | QHCW2015 | — | QHCW3015H | — |
| 20 | QHCW1020 ① | QHCW2020 | — | QHCW3020H | — |
| 25 | QHCW1025 | QHCW2025 | — | — | — |
| 30 | QHCW1030 | QHCW2030 | — | — | — |

Notes

① Switching duty rated for 120 Vac fluorescent light applications only.

 Non-automatic switches, see **Page V4-T1-41**.