



Catalog No. THQC2190WL

Description: 2P 120/240V 10K IC 90 AMP W/LUGS

UPC No 783164131574

$\label{eq:continuous} \mbox{Products} > \mbox{Circuit Breakers} > \mbox{Mini} \mbox{ Circuit Breakers} > \mbox{Q-Line} \\ \mbox{Miniature Circuit Breakers}$

Q line circuit breakers are one-inch wide per pole, compact, thermal-magnetic devices designed for residential and commercial applications. The QC breakers are lug-lug versions of the Q Line and are available for 35mm DIN rail mounting. All Q Line circuit breakers feature Quick-make / Quick-break mechanisms, common trip bars, and easy to spot trip indication to ensure safety and reliability. Q Line breakers are available in 1, 2, and 3 pole versions and can be ordered with auxiliary contact and shunt trip accessories.

Descriptors	
Category	Q-Line Miniature Circuit Breakers
GO Schedule	EB
Specifications	
Trip Style	Non-Interchangeable
Frame Type	Q-Line
A mana a ma	00.4

Trip Style	Non-Interchangeable
Frame Type	Q-Line
Amperage	90 A
System Voltage	120 Vac, 120/240 Vac
Poles	2
Trip Function	Ц
Continuous Current Rated	Standard
120 Vac Interrupting Rating	10 KAIC
120/240 Vac Interrupting Rating	10 KAIC
Suitable for Reverse Feed	Yes
Product Line	Q-Line (Lug-Lug)
Long Time	Fixed
Instantaneous	Fixed
Protective Relays	No
Current Metering	No

Classifications	
UL File #	E11592

HACR

No

geindustrial.com Created on: 08/28/2017

Special Markings GSA Compliance

Publications Title Publication No. Publication Type Q-Line Lug-Lug MCCB, 100A Frame 1-, 2-, or 3- Pole, Drawing 1-Page fully dimensioned outline drawing in .pdf format 455C874-SH1 Dimensional

Additional Documentation: Visit our <u>Publication Library</u> to find technical documentation, time current curves, CSI Specifications and promotional literature.

geindustrial.com Created on: 08/28/2017