

# **EVERPURE**<sup>°</sup> CLARIS SMALL FILTER CARTRIDGE

## ADJUSTABLE ION-SELECTIVE FILTERS TO TAILOR CARBONATE HARDNESS LEVELS IN POTABLE WATER

Claris Small Filter Cartridge: EV4339-10



### **APPLICATIONS**

Coffee Espresso Hot Drink Vending Combi Steamers

### **FEATURES • BENEFITS**

Removes harmful contaminants and unpleasant odors and tastes

Removes particles down to five (5) micron for highest equipment protection

Operation in vertical or horizontal position

Self-Cooking Systems Steam Cookers and Ovens Brewed Iced Tea

Five-stage filtration process:

- Prefiltration
- Carbonate hardness adjustment
- Fine filtration
- Highly efficient carbon block
- Solid membrane filter

### **INSTALLATION TIPS**

The system can be operated freestanding, lying horizonally or mounted vertically.

If mounting vertically to a wall, securely connect the mounting backet to the wall using suitable screws.

Water pressure at the filter system inlet must not exceed 116 psi (8 bar). A pressure reducer valve must be installed on the water supply side of the filter system if the inlet pressure exceeds 116 psi (8 bar).

Shut-off valve must be installed upstream of the filter.

Refer to Installation, Operation & Maintenance Manual for cartridge flushing and startup.

**OPERATION TIPS** 

Change Claris Cartridges when its pre-calculated water volume has been reached or at least once per year.

Change cartridges when capacity is reached.

Always flush the filter cartridge at time of installation and cartridge change.

Do not use hardness test strips to check for hardness reduction. Please use the Claris Titration Kit (EV4339-40) to check for hardness reduction.


### SIZING

Service Flow Rate: Maximum 0.5 gpm (2 Lpm)

Rated Capacity: 400 gallons (1,514 L) for Espresso and 450 gallons (1,703 L) for OCS/Coffee\*

\*This capacity is based on influent water hardness of 180 ppm with standard bypass settings. For steam applications and other hardness levels consult installation and operations guide capacity and bypass settings charts.

# **EVERPURE**<sup>®</sup> CLARIS SMALL FILTER CARTRIDGE EV4339-10



### **SPECIFICATIONS**

Service Flow Rate Maximum 0.5 gpm (2 Lpm)

### **Rated Capacity**

400 gallons (1,514 L) for Espresso and 450 gallons (1,703 L) for OCS/Coffee\*

\*This capacity is based on influent water hardness of 180 ppm with standard bypass settings. For steam applications and other hardness levels consult installation and operations guide capacity and bypass settings charts.

**Pressure Requirements** 29 - 116 psi (2 – 8 bar), non-shock

**Temperature Limits** 39 - 86°F (4 - 30°C)

**Overall Dimensions** 12.39" L x 3.74" D (31.5 cm x 9.4 cm)

Claris™ is a trademark of Aquis, GmbH

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

### WARRANTY

Everpure water treatment systems by Pentair® (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. Everpure replaceable elements (filter catridges and water treatment catridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Pentair will provide a copy of the warranty upon request.



### WATER QUALITY SYSTEMS

EVERPURE-SHURFLO WORLD HEADQUARTERS, 1040 MUIRFIELD DRIVE, HANOVER PARK, IL 60133 USA • FOODSERVICE.PENTAIR.COM 800.942.1153 MAIN (US ONLY) • 630.307.3000 MAIN • 630.307.3030 FAX • CSEVERPURE@PENTAIR.COM EMAIL EVERPURE-SHURFLO AUSTRALIA, 1-21 MONASH DRIVE, DANDENONG SOUTH, VIC 3175, AUSTRALIA 011.1300.576.190 TEL • 011.61.39.562.7237 FAX • AU.EVERPURE@PENTAIR.COM EMAIL EVERPURE-SHURFLO CHINA, 21F CLOUD 9 PLAZA, NO 1118, SHANGHAI, 200052, CHINA 86.21.3211.4588 TEL • 86.21.3211.4580 FAX • CHINA.WATER@PENTAIR.COM EMAIL EVERPURE-SHURFLO INDIA, GREEN BOULEVARD, B-9/A, 7TH FLOOR - TOWER B SECTOR 62, NOIDA - 201301 91.120.419.9444 TEL • 91.120.419.9400 FAX • INDIACUSTOMER@PENTAIR.COM EMAIL EVERPURE-SHURFLO EUROPE, PENTAIR WATER BELGIUM BVBA, INDUSTRIEPARK WOLFSTEE, TOEKOMSTLAAN, 30 B-2200 HERENTALS, BELGIUM +32.[0].14.283.500 TEL • +32.[0].14.283.505 FAX • SALES@EVERPURE-EUROPE.COM EMAIL EVERPURE-SHURFLO JAPAN INC., HASHIMOTO MN BLDG. 7F, 3-25-1 HASHIMOTO, MIDORI-KU, SAGAMIHARA-SHI KANAGAWA 252-0143, JAPAN 81.[0]42.775.3011 TEL • 81.[0]42.775.3015 FAX • INFO@EVERPURE.CO.JP EMAIL EVERPURE-SHURFLO SOUTHEAST ASIA, SOUTHEAST ASIA, 390 HAVELOCK ROAD, #04-01, KING'S CENTRE, SINGAPORE 169662 65.6788.5800 TEL • 65.6737.5149 FAX • CSEVERPURE@PENTAIR.COM EMAIL All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.