

ROM II Reverse Osmosis System

Delivers premium quality RO water for drinking water applications

EV9273-70



ROM II System: EV9273-75 S-101 Cartridge: EV9273-77 TFC Cartridge: EV9273-70

BENEFITS

Comprehensive water filtration and treatment technology delivers ultra clear, fresh, premium quality drinking water

Reduces lead, nitrates, arsenic, and fluoride, plus reduces barium, cadmium, mercury, TDS and other dissolved solids and heavy metals

Reduces chlorine taste and odor and other contaminants

Reduces possible health hazards such as asbestos fibers and other potentially harmful contaminants, such as Cryptosporidium and Giardia Cysts

Reduces scale build-up that can clog appliances

Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination

Compact, under-sink sizing

NSF Certified under NSF Standard 58 and WQA Gold Seal validated

INSTALLATION TIPS

This system must be installed and maintained according to the manufacturer's instructions, including installation and replacement of filter cartridges

Install vertically with cartridge hanging down

Allow 2-1/2" clearance below the cartridges for easy cartridge replacement

Flush system by running water through cartridges per Installation and Use manual

OPERATION TIPS

Change S-101 Cartridge (A) every 300 gallons or 6 months

Change TFC Cartridge (B) every 2 years

Always flush the filter cartridges at time of installation and cartridge change

APPLICATION/SIZING

For office water applications

Nominal production rate: Varies depending on specific water conditions

SPECIFICATIONS

Overall System Dimensions: 19-1/2"H x 8"W x 4"D

Inlet connection:

3/8" FPT

Outlet connection:
Ouick Connect

Pressure Requirements:

40 psig -125 psig (2.8 - 8.6 bar)

Maximum Temperature: 40°F - 100°F (4-38°C)


Shipping Weight:

9 lbs.

Operating Weight:

6 lbs.

ROM II Reverse Osmosis System



WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



System Tested and Certified by NSF International against NSF/ANSI Standard 58 for the reduction of:

Arsenic, Barium, Cadmium, Copper, Cyst, Fluoride, Hexavalent Chromium, Lead, Nitrate/Nitrite, Radium 226/228, Selenium, TDS, Trivalent Chromium



EVERPURE, LLC
1040 Muirfield Drive
Hanover Park, Illinois 60133
Toll Free (800) 323-7873
Tel (630) 307-3000
Fax (630) 307-3030
http://www.everpure.com

In Europe: N.V. EVERPURE (EUROPE) S.A. Industriepark Wolfstee Toekomstlaan 30 B-2200 Herentals Belgium

Tel 32 -14-283500 Fax 32-14-283505 In Japan:
EVERPURE JAPAN LLC
HASHIMOTO MN BLDG. 7F
3-25-1 HASHIMOTO SAGAMIHARA-SHI
KANAGAWA 229-1103
JAPAN
Tel 81-(0)42-775-3011
FAX 81-(0)42-775-3015

Everpure 1040 Muirfield Drive Hanover Park, IL 60133

Phone: 630-307-3020 Fax: 630-307-3030