Efilters.net Everpure Residential Cartridges Cross Reference

SPECIFICATIONS	S54	H54	ADC	AC	EF1500	S100	S104	H104	H1200	PBS400	EF3000	H300	H300-HSD	H300-NXT	EF6000
Cartridge length in inches*	12"	12"	12"	12"	12"	16"	16"	16"	16"	16"	16"	20"	20"	20"	20"
Flow rate in gallons per minute (gpm)	0.5	0.5	0.5	0.5	2.2	0.5	0.5	0.5	0.5	2.2	2.2	0.5	0.5	0.5	2.2
Capacity in US gallons	750	750	750	750	1500	1500	1000	1000	1000	3000	3000	300	300	300	6000
Bottled Water Equivalent (in 500 ml. /16.9 oz. bottles)	5680	5680	5680	5680	11,360	11,360	7573	7573	7573	22,721	22,721	2272	2272	2272	45,442
Limescale Reduction		X			X			X	X	X	X	X	X	X	X
Dirt/Rust Reduction	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
Bacteriostatic Control			X						X			X	X	X	X
Oxidized iron, manganese & sulfides reduction	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
MTBE Reduction									X						
NSF Std. 42 for Chlorine Reduction Class 1	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
NSF Std. 42 for Particulate Reduction Class 1	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
NSF Std. 53 for Cyst Reduction	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
NSF Std. 53 for Lead Reduction	X	X			X	X	X	X	X	X	X	X	X	X	X
NSF Std. 53 for VOC & THM Reduction									X			X	X	X	
NSF Std. 401 for Emerging Contaminants														X	
Note: Cartridge length includes an additional 3" inches required for cartridge removal															
There are no interchangeable cartridges for the H1200															