HARMSCO[®] Calypso Blue[™] Cartridges

Industrial and Residential

Premium and WaterBetter Series

Designed for 4-1/2" diameter filter housings.

Highly efficient filter cartridges available in a selection of media including the industry's largest surface area.



Lower overall operating cost
 Longer filter runs for fewer change outs
 Lower initial pressure drops
 Reduced maintenance down time and cost
 Increased contaminant removal
 High flow capability

Features

- Pleated design for more surface area
- FDA approved materials NSF 61 certified
- Engineered media for superior performance
- Cleanable and reusable in most applications and micron sizes
- Thermally bonded end caps to ensure better sealing
- Full product line largest selection of micron ratings
- Optional High Temperature cartridges available



Applications

- Reverse Osmosis Pre-filtration
- Municipal Drinking Water Filtration
- Commercial/Residential Drinking Water Filtration
- Desalination Pre-filtration
- Industrial Water Filtration

- Cooling Tower Filtration
- Chill Water Loop Filtration
- Food & Beverage Filtration
- Marine/Aquatic Filtration



HARMSCO[®] Filtration Products

Shrink Wrap: Standard on all Premium

and WaterBetter Calypso cartridges **Temperature:** up to 140°F (60°C)

20"

Center Tubes: ABS or PVC

Calypso Blue[™] Cartridges

NSE

Certified to ANSI-NSF 61

Specifications

- Nominal Micron Ratings: 0.35, 1, 5, 20, 50 microns; Absolute Micron Rating: 1 micron
- Filter Media: Polyester Plus, Synthetic Fiber
- End Caps: Pliable PVC or Urethane

Cartridge Selection/Sizing Guide 9-3/4"

| Product Code | Nominal | Media | Maximum | Length | 0.D. | No./Case |
|----------------------------|---|---------------------|------------------|--------|-------|----------|
| | Micron Rating eered for high efficiency, low | (sq ft) | Flow Rate* (GPM) | (in) | (in) | |
| HB-10-0.35W | | 12 | 12 | 9-3/4 | 4-1/2 | 8 |
| HB-10-0.35W HB-10-1W | 1 | 12 | 12 | 9-3/4 | 4-1/2 | 8 |
| HB-10-5W | 5 | 12 | 12 | 9-3/4 | 4-1/2 | 8 |
| HB-10-20W | 20 | 12 | 12 | 9-3/4 | 4-1/2 | 8 |
| HB-10-50W | 50 | 12 | 12 | 9-3/4 | 4-1/2 | 8 |
| HB-20-0.35W | 0.35 | 26 | 26 | 20 | 4-1/2 | 4 |
| IB-20-1W | 1 | 26 | 26 | 20 | 4-1/2 | 4 |
| HB-20-5W | 5 | 26 | 26 | 20 | 4-1/2 | 4 |
| 1B-20-20W | 20 | 26 | 26 | 20 | 4-1/2 | 4 |
| 1B-20-50W | 50 | 26 | 26 | 20 | 4-1/2 | 4 |
| | 100% synthetic composite | media | | | | |
| HB-10-1W-HF | 1 | 8 | 8 | 9-3/4 | 4-1/2 | 8 |
| 1B-10-1W-HF 1B-10-5W-HF | 5 | 8 | <u> </u> | 9-3/4 | 4-1/2 | 8 |
| | - | _ | - | | | - |
| HB-10-20W-HF | 20 | 8 | 8 | 9-3/4 | 4-1/2 | 8 |
| HB-20-1W-HF | 1 | 20 | 20 | 20 | 4-1/2 | 4 |
| IB-20-5W-HF | 5 | 20 | 20 | 20 | 4-1/2 | 4 |
| HB-20-20W-HF | 20 | 20 | 20 | 20 | 4-1/2 | 4 |
| | cron absolute, multi-layed m | edia | | | | |
| PP-BB-10-1 | 1 | 8 | 4 | 9-3/4 | 4-1/2 | 8 |
| PPFS-BB-10-1 | 1 | 8 | 4 | 9-3/4 | 4-1/2 | 8 |
| PP-BB-20-1 | 1 | 20 | 10 | 20 | 4-1/2 | 4 |
| PPFS-BB-20-1 | 1 | 20 | 10 | 20 | 4-1/2 | 4 |
| SureSafe Antin | nicrobial - reduces grow | wth of bacteria and | mold on media | | | |
| HB-10-20W-AM | 20 | 12 | 12 | 9-3/4 | 4-1/2 | 8 |
| HB-10-50W-AM | 50 | 12 | 12 | 9-3/4 | 4-1/2 | 8 |
| IB-20-20W-AM | 20 | 26 | 26 | 20 | 4-1/2 | 4 |
| HB-20-50W-AM | 50 | 26 | 26 | 20 | 4-1/2 | 4 |
| EZ-Clean - 100% | synthetic composite 50 micr | on media | | | | |
| HB-10-EZ-CLEAN | 30 | 12 | 12 | 9-3/4 | 4-1/2 | 8 |
| HB-20-EZ-CLEAN | 30 | 26 | 26 | 20 | 4-1/2 | 4 |
| | | | | _ ~ | | |
| WaterBetter Po | blyester - economy grad | le | | | | |
| VB-HB-10-1W | 1 | 9.5 | 10 | 9-3/4 | 4-1/2 | 8 |
| VB-HB-10-5W | 5 | 9.5 | 10 | 9-3/4 | 4-1/2 | 8 |
| VB-HB-10-20W | 20 | 9.5 | 10 | 9-3/4 | 4-1/2 | 8 |
| VB-HB-10-50W | 50 | 9.5 | 10 | 9-3/4 | 4-1/2 | 8 |
| VB-HB-20-1W | 1 | 21 | 20 | 20 | 4-1/2 | 4 |
| VB-HB-20-5W | 5 | 21 | 20 | 20 | 4-1/2 | 4 |
| WB-HB-20-20W | 20 | 21 | 20 | 20 | 4-1/2 | 4 |

* Harmsco recommends operation at 50-70% of maximum flow rate for optimum performance.

50

Note: This publication is to be used as a guide. The data within has been obtained from many sources and is considered to be accurate. Harmsco does not assume liability for the accuracy and/or completeness of this data. Changes to the data can be made without notification. Temperature, Pressure, Flow Rates, Differential Pressures, Chemical Combinations and other unknown factors can affect performance in unknown ways. Limited Warranty: Harmsco warrants their products to be free of material and workmanship defects. Determination of suitability of Harmsco products for uses and applications contemplated by Buyer shall be the sole responsibility of Buyer. The end user/installer/buyer shall be liable for the product's performance and suitability regarding their specific intended applications. End users should perform their own tests to determine suitability for each application.

20

HARMSCO[®] Filtration Products

www.harmsco.com

20



4

P.O. Box 14066, North Palm Beach, FL 33408 (561) 848-9628 • Toll-free: (800) 327-3248 • Fax: (561) 845-2474 • E-mail: sales@harmsco.com

21

© Harmsco, Inc. 32B 2/11

4 - 1/2

WB-HB-20-50W