10 THINGS YOU SHOULD KNOW...

- 1. Ensure stabilizing foot screws are tightened all the way before use.
- 2. Clear your tank of leaves and other debris before placing your Aeromixer and filling with water.
- 3. For ease of set up, place your Aeromixer in an empty tank. Ensure that your Aeromixer is placed against the sidewall of your tank, with both tips of the green stabilizing foot making contact with the sidewall.
- 4. Nutrients should be added slowly when your Aeromixer is running in a full tank of water. No more than a 1/4 pound of dry nutrients per gallon of water can be added to your mixing tank. (Oversaturation of Nutrients can cause hydrolock and will void warranty of your Aeromixer.)
- 5. Never lift your Aeromixer by its air intake hose or by the power cord.
- 6. Don't start your Aeromixer unless it is submerged in at least 5 1/2" of water.
- 7. The end of the air intake hose must be out of the tank to inject air. Make sure the air intake hose is not kinked and is clear of debris.
- 8. Aeromixer is not designed for continuous use. Recomended run times are as follows: (*Please note every tank and environment is different and may require time adjustments. Please contact us if you have any temperature issues.*)

Tank size (Gallons) Time to run Aeromixer Time to let tank rest

50-100 gallons 100-250 gallons 250-500 gallons 500-1000 gallons 1000-3000 gallons	15 minutes on 30 minutes on 1 hour on 2 hours on	2 hours off 2 hours off 2 hours off 2 hours off
1000-3000 gallons	4 hours on	2 hours off

- 9. Cleaning your Aeromixer regularly is important. See page 9 for detailed instructions.
- 10. Never service or move your Aeromixer while it is plugged in.