Bluelab

29/06/2021

0		
Product Name:	Bluelab PeriPod L3	
Product Code:	PERIPODL3	
UPC Code:	9421024920883	
Country of Origin:	New Zealand	
Tariff Code:	9027.80	
Shipping Quantity:	Sold as singular unit	
Packaging Information:		
Packaged Weight:	4.9 kg / 10.8 lb	
Packaged Length:	420 mm / 16.54 in	
Packaged Width:	290 mm / 11.42 in	
Packaged Height:	260 mm / 10.24 in	

Sales Description:

NOTE: this copy can be used in brochures, catalogues or online

Confidently automate the perfect pH and nutrient levels, for growing reservoirs

Easy integration for nutrient solution management.

Your time is extremely valuable, don't waste it manually dosing. Designed to be teamed with the Bluelab® Pro Controller for a fully integrated solution for optimal reservoir dosing, the Bluelab® PeriPod[™] is a simple and reliable inclusion.

The Bluelab® PeriPod[™] responds to dosing triggers received from the Bluelab® Pro Controller and pumps pH adjusters and nutrient stock solutions into your reservoir using peristaltic pumps. Accurately measure, control and maintain pH levels. Grow sites are all different so now you can choose the size to match your set up needs and add optional extras, external alarm box and sample pot, to your nutrient dosing system set up.

Visit the Bluelab® PeriPod™ pages on bluelab.com to read more about which pump size is suitable for your system.

Register your product here: http://bluelab.com/product-registration

Features:

L Versions:

- 1x 1200ml (40fl oz)/min peristaltic pump for dosing pH adjuster solutions
- 2x 1200ml (40fl oz)/min peristaltic pumps for dosing nutrient stock
- solutions
- Rugged wall mount design
- Individual pump priming and calibration
- Replaceable peristaltic pumps and tubing
- Compatible with Bluelab® Pro Controller™ and most Bluelab®
 Dosetronic™ models

Length: 392 mm / 15.4 in Height: 154 mm / 6 in

Product Guarantee:

Two year limited guarantee, proof of purchase required. Six months for pumps & tubing



Product images available for Screen or Web use:

Bluelab-PeriPod-L3-Front-Web.jpg Bluelab-PeriPod-L3-Front-Web-sml.jpg Bluelab-PeriPod-L3-WEB.jpg Bluelab-PeriPod-L3-WEB-sml.jpg

Product images available for PRINT: Note: these images are high resolution in CMYK.

Bluelab-PeriPod-L3-Front-MR-flat-cmyk Bluelab-PeriPod-L3-flat-MR-cmyk

Technical Specifications:	
Default Pump Function:	#1: pH, #2: EC A, #3: EC B
Pump Flow Rate per Minute:	
Solution Temperature:	5 - 50°C, 41 - 122°F
Environment Temperature:	5 - 40°C / 41 - 104°F
Flow Rate Accuracy at 25°C or 77°F:	±10%

2

YEAR