

20" VERSA-KOOL CIRCULATION FAN

VK20-GA-3

Product Description

Reduce heat stress and improve air quality with Schaefer's uniquely designed circulation fans. Unrivaled in the market, these fans are engineered to produce greater air movement and superior cooling no matter the application. You don't hear them. You don't see them. You only feel them!

Also known as Horizontal Air Flow (HAF) fans, these fans move air in a coherent horizontal pattern creating a gentle 'racetrack' air flow pattern needed in greenhouses to maximize heat distribution and humidity control by mixing the air, from ceiling to floor.

Features

Deep guard design for unmatched performance, low noise levels and safety without sacrificing airflow

Matched high quality motors and blades for maximum efficiency

Powder coated steel guards for increased durability and corrosion resistance

Hot dipped galvanized guards on VK12-GA and VK20-GA models for even greater rust protection

Powder coated steel mounting bracket included

Wide variety of mounting options available for flexible and easy installation

Variable speed controls available

Misting kits available for even greater cooling

Two year warranty

Made in the USA

Specifications

Air Velocity (@ 10')	TBD
Blade Color	Metallic
Brand	Schaefer
Cfm (free Air)	TBD
Drive	Direct
Enclosure	TEAO
Frame Size	48
Phase	3
Speeds	1
Vfd Compatible	No

Frequency (hz)	60/50
Guard Color	Metallic
Nameplate Amps	3.0/1.5
Number Of Wings	3
Power (hp)	1/2
Product Dimensions (L X W X H Inches)	TBD
Product Net Weight (lbs)	37
Switch	Not included

Product Color	White
Product Shipping Dimensions (in)	23x23x18
Speed Control Compatible?	No
Cfm Range (free Air)	TBD
Distinguishing Feature	Highly Corrosion Resistant
Fixed Or Portable	Fixed
Guard Material	Galvanized



Cfm/watt (free Air)	TBD
Cord	Not included
Diameter (inches)	20

Voltage	230/460
Air Velocity (@ 5 Times Diameter)	TBD
Blade Material	Aluminum
Cfm (high)	TBD
Cfm Calculation Standard	ANSI/AMCA Standard 230-99

	Steel
Oscillating	No
Rpm 50 Hz Motor	1350-1500
Country Of Origin	US
Guard Spacing (inches)	1/2 - 1 UL507
Cfm/watt (@0.10")	TBD
Cfm/watt (@0.05")	TBD