



2023 MARKS THE ARRIVAL OF THE



Patent Pending

If the **ingenious ease of installation** remains the key feature of this second generation, brand-new attributes come to reinforce its stability and sealing properties.

QUICK AND EASY INSTALLATION

Simple and intuitive installation procedure done in no time.

- 1. Clip
- 2. Drill
- 3. Turn
- 4. Screw
- Innovative integrated positioning and drilling template:
 - Extremely practical and unique template in the market,
 - Consistently positions the inlet at the ideal angle of 55 to 60 degrees,
 - Facilitates the installation of the lateral line and extends its integrity.
- Installs on any mainline with a diameter corresponding to the FLEXCLIP™ 2.0.



IMMOBILITY OF FLEXCLIP™ 2.0

- Protruding Chimney:
- Prevents any movement of the FLEXCLIP[™] 2.0 on the mainline,
- The "click" sound simplifies the final placement of the FLEXCLIP™ 2.0.

MAINLINE INTEGRITY

 Since it rests on 87% of the mainline's circumference, the FLEXCLIP[™] 2.0 allows the tubing to maintain good circularity.

PROVEN SELF-ADHESIVE SEAL

- Made of food-grade silicone.
- Firmly pre-installed at the factory.
- New optimized dimensions for proven sealing.
- Receiving cavity:
- Compact cavity that securely immobilizes the self-adhesive seal.
- Bumpers that consistently ensure the ideal compression of the seal for optimal waterproofing.

DIMENSIONS

- 1 inch
- Other sizes available soon

STAINLESS STEEL SCREW



