

# Scotch®

## High Tack Box Sealing Tape 375+

### Confident world traveler.

Introducing the high-performance tape  
that seals securely for safe arrival.



# 3M™

# Confidently withstand the toughest ecommerce packaging challenges.


The ecommerce supply chain journey is subject to challenges at every step: hard to seal boxes, line slow downs, tampering, and open package returns. Scotch® High Tack Box Sealing Tape 375+ was created as part of the 3M total system solution to help solve these problems, so you can be confident your packages will stay securely sealed all the way to their destination.

► **Securely seal hard-to-stick boxes**

Keeps recycled corrugated boxes **securely sealed** under challenging ecommerce shipping, storage and delivery conditions.

► **Package security**

Strong adhesive bond to the box helps **prevent tampering** and tape failure during shipping and delivery.



Can't reach in under the flap.

► **Keep the line moving efficiently**

Apply by hand, semi-automatic and automatic dispensers, virtually jam free. Sticks at first application keeping parcels closed down the entire packaging line, allowing **more boxes per minute**.

► **Reduce concession rates**

Have confidence your boxes will **remain sealed** during transport, reducing open package returns.



What operators are saying:

**“375+ is amazing! Our packages stay sealed, making our customers happy! It's a huge confidence booster!”**

## Strong initial bond keeps corrugated packages closed, even under crushing delivery conditions.


Bottom to top, Scotch® High Tack Box Sealing Tape 375+ will keep stacked packages sealed and secure.



Scotch® High Tack Box Sealing Tape 375+



Competitor A



Competitor B

**Fiber Pull Demonstration:** Shows how much paper fiber the tape pulls off the recycled corrugate box upon removal. The higher percent of fiber pull, the stronger the tape bond is to the box.

Product	Tape Structure (Backing / Adhesive)	Adhesion to Steel oz./in. (N/100mm)	Tensile Strength lbs./in. (N/100mm)	Elongation at Break (%)	Total Thickness mils (mm)	Available Widths	Color
<b>ASTM Test Method</b>		<b>D-3330</b>	<b>D-3759</b>	<b>D-3759</b>	<b>D-3652</b>		
<b>Scotch® High Tack Box Sealing Tape</b>							
<b>375+</b>	Polypropylene / Hot melt rubber-resin	55 (60)	35 (613)	160	3.1 (0.079)	48mm 72mm	Clear Can be custom printed

**Note:** This technical information and data should be considered representative or typical only and should not be used for specification purposes.



### 3M Closure and Masking Systems Division

3M Center, Building 225-3S-06  
St. Paul, MN 55144-1000  
800-362-3550 877-369-2923 (Fax)

**Warranty and Limited Remedy:** 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. **Limitation of Liability:** Except for the limited remedy above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential, regardless of the legal or equitable theory asserted.

Scotch is a registered trademark of 3M. 3M, 3M-Matic and the Plaid are trademarks of 3M. © 3M 2019. All rights reserved. Please recycle. 70-0716-9782-8.