


Sockets

for internal square 3/8" or 1/2"
IEC 60900 DIN EN 60900





98

- > 12 points of contact
- > for imperial hexagonal head screws
- > chrome plated
- > chrome vanadium steel



98 47 1/2"
1000 V  



Product Number	Packaging	↔ Inch mm		Width across flats S Inch	dia. of effective tool side d max. Inch	Square drive Inch	⚖ lbs
98 37 1/2"		1 49/64 45	1000 V  	1/2	57/64	3/8	0.09
98 37 3/4"		1 59/64 49		3/4	1 3/16	3/8	0.14
98 37 3/8"		1 21/32 42		3/8	47/64	3/8	0.07
98 37 5/16"		1 21/32 42		5/16	5/8	3/8	0.07
98 37 5/8"		1 13/16 46		5/8	1 1/32	3/8	0.11
98 37 7/16"		1 11/16 43		7/16	25/32	3/8	0.08
98 37 9/16"		1 27/32 47		9/16	15/16	3/8	0.09
98 47 1"		2 13/32 61	1000 V  	1	1 19/32	1/2	0.38
98 47 1/2"		2 11/64 55		1/2	29/32	1/2	0.15
98 47 11/16"		2 11/64 55		11/16	1 7/64	1/2	0.18
98 47 3/4"		2 11/64 55		3/4	1 13/64	1/2	0.19
98 47 5/8"		2 11/64 55		5/8	1 1/16	1/2	0.19
98 47 7/8"		2 9/32 58		7/8	1 23/64	1/2	0.26
98 47 9/16"		2 11/64 55		9/16	31/32	1/2	0.16