


950 L-key, metric, chrome-plated, 7 x 95 mm

L-Keys for Hexagon Socket Screws



<b>EAN:</b>	4013288018359	<b>Size:</b>	95x34x8 mm
<b>Part number:</b>	05021050001	<b>Weight:</b>	41 g
<b>Article number:</b>	950	<b>Country of origin:</b>	CZ
		<b>Customs tariff number:</b>	82041100

- L-keys for hexagonal socket screws
- Wear-resistant size marking
- L-keys with Hex-Plus advantage for a longer screw life
- High corrosion protection thanks to chrome-plating
- Metric

High quality L-keys for hexagonal socket screws. Hex-Plus offers a larger contact surface within the screw head. This reduces the notching effects to a minimum and almost completely eliminates the risk of destroying the screw recess. The precise chrome-plated design ensures high corrosion protection.

**Web link**

[https://products.wera.de/en/l-keys\\_l-keys\\_for\\_hexagon\\_socket\\_screws\\_950.html](https://products.wera.de/en/l-keys_l-keys_for_hexagon_socket_screws_950.html)

Wera - 950  
05021050001 - 4013288018359

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

## L-Keys for Hexagon Socket Screws

### L-Keys



We questioned the classic L-key design, since all too often the screw head recess is rounded out, meaning screws can no longer be tightened or loosened - and so the user finds the L-key slipping out of the recess. Wera Hex-Plus tools have a larger contact surface in the screw head. The notching effects are reduced and thereby the deformation of the screws. At the same time, as much as 20 % more torque can be applied.

### Hex-Plus



Hexagon screws can endure a problem because the contact surfaces delivering the power from the conventional tool, is transferred to the screw via very small surface areas. The consequence: the screw can become damaged (rounding out). Hex-Plus tools have a greater contact surface that prevents this from happening! At the same time, as much as 20 % more torque can be applied. Good to know: Hex-Plus tools fit into every standard hexagon socket screw!

### Size identification



The size of each L-keys has been engraved by a laser. In addition Take it easy L-keys have a colour coding according to sizes - for simple and rapid accessing of the required tool. Making it easy to find the right tool.

### Surface protection



Chrome-plated hexagon L-keys for outstanding surface protection and long service life. High corrosion protection.

### Web link






[https://products.wera.de/en/l-keys\\_l-keys\\_for\\_hexagon\\_socket\\_screws\\_950.html](https://products.wera.de/en/l-keys_l-keys_for_hexagon_socket_screws_950.html)

Wera - 950  
05021050001 - 4013288018359

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

## L-Keys for Hexagon Socket Screws

Further versions in this product family:

					
	mm	mm	mm	inch	inch
05021005001 <sup>1)</sup>	1.5	45	14	1 3/4"	9/16"
05021010001	2.0	50	16	2"	5/8"
05021015001	2.5	56	18	2 7/32"	23/32"
05021020001	3.0	63	20	2 1/2"	25/32"
05021025001	3.5	66	23	2 5/8"	29/32"
05021030001	4.0	70	25	2 3/4"	1"
05021035001	4.5	75	26	3"	1 1/32"
05021040001	5.0	80	28	3 1/8"	1 3/32"
05021045001	6.0	90	32	3 1/2"	1 1/4"
<b>05021050001</b>	<b>7.0</b>	<b>95</b>	<b>34</b>	<b>3 3/4"</b>	<b>1 5/16"</b>
05021055001	8.0	100	36	4"	1 7/16"
05021060001	9.0	106	38	4 3/16"	1 1/2"
05021065001	10.0	112	40	4 7/16"	1 9/16"
05021070001	11.0	120	43	4 3/4"	1 11/16"
05021075001	12.0	125	45	5"	1 3/4"
05021080001	13.0	132	50	5 3/16"	2"
05021085001 <sup>1)</sup>	14.0	140	56	5 1/2"	2 7/32"
05021090001 <sup>1)</sup>	17.0	160	63	6 5/16"	2 1/2"
05021095001 <sup>1)</sup>	19.0	180	70	7 1/16"	2 3/4"

1) Regular hexagon.

## Web link

[https://products.wera.de/en/l-keys\\_l-keys\\_for\\_hexagon\\_socket\\_screws\\_950.html](https://products.wera.de/en/l-keys_l-keys_for_hexagon_socket_screws_950.html)

Wera - 950

05021050001 - 4013288018359

Wera Werkzeuge GmbH

Korzter Straße 21-25

D-42349 Wuppertal

Tel: +49 (0)2 02 / 40 45-0

E-Mail: info@wera.de