



- L-keys for recessed TORX® screws
- The holding function on the long arm keeps screws securely on the tool
- Extremely high corrosion protection thanks to ice-hardened stainless steel design
- · Handle-friendly hose jacket with tool finder "Take it easy": Colour coding according to size

High quality stainless steel L-key for internal TORX® screws. Very corrosion-resistant due to ice-hardened stainless steel material of the L-key, avoiding the transmission of extraneous rust in stainless steel screw connections. With holding function on the long arm: The clamping force resulting from the surface pressure between the output tip and the screw profile holds the screws securely on the tool. With extra long arm for working in a low position. The grip-friendly hose jacket facilitates screwdriving even at low temperatures. "Take it easy" tool finder with colour coding by size.



## Stainless L-keys

EDELSTAHL (® Rost frei INOX STAINLESS STEEL

Stainless L-keys are hardened to the same strength as conventional (carbon) steel tools, and prevent extraenous rust forming.

With sleeve



L-keys with a thermoplastic sleeve are manufactured out of easy-togrip, circular material. The sleeve ensures that work is safe and comfortable even at low temperatures. Colour coding and large stamp to enable the desired L-key to be easily located.

## Holding function for recessed TORX® screws



The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that TORX® screws made according to Acument Intellectual Properties specifications are securely held on the tool!

## Take it easy tool finder system



Take it easy tool finder system with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

		$\mathbf{O}$	L V		L V	
			mm	mm	inch	inch
05022680001	iceblue_277C	TX 8	90	16	3 1/2"	5/8"
05022681001	tuerkis_339C	TX 9	101	16	4"	5/8"
05022682001	leuchtgruen_375C	TX 10	112	19	4 7/16"	3/4"
05022683001	leuchtgelb_yellow C	TX 15	123	21	4 7/8"	27/32"
05022684001	pink_241C	TX 20	137	24	5 3/8"	1"
05022685001	gelb_123C	TX 25	154	27	6 1/16"	1 1/16"
05022686001	blau_307C	TX 27	172	31	6 3/4"	1 1/4"
05022687001	leuchtorange_152C	TX 30	195	37	7 11/16"	1 7/16"
05022688001	rot_200C	TX 40	224	42	9"	1 11/16"

## Further versions in this product family: