
Kraftform Plus - Series 300



H Wera Be + TOOL Rebel







- Nutsetter for hexagon head screws
- Multi-component Kraftform handle for fast and ergonomic screwdriving
- Handle markings simplify finding and sorting of tools
- Hexagonal anti-roll feature against rolling away
- Hollow shaft for protruding threaded rods, chrome-plated

Premium Wera insert wrench screwdriver with hollow shaft for screwdriving on thread rods, because only then can the thread rod penetrate through the bolt into the hollow shaft of the screwdriver. Multi-component Kraftform handle for high working speeds and particularly ergonomic screwdriving. Kraftform Plus: Hard handle zones for high working speeds, while soft handle zones guarantee a high torque transfer. With hexagon anti-roll protection against rolling away. Handles marked for easy identification and sorting of tools. For external hexagon screws.

395 HO Nutdriver, 3/8" x 90 mm

Kraftform Plus – Series 300



Hollow shaft nutsetter

Kraftform

Rapid hand repositioning



shaft Hollow for protruding threaded rods



A screwdriver with a hollow shaft is needed whenever there are screwdriving jobs involving threaded rods i.e. the threaded rod through the nut can slip into the hollow shaft of the screwdriver.



The basic idea for the prototype of the Kraftform handle - that the hand should dictate the design has, right through to today, proved to be correct. In cooperation with internationally recognised the Fraunhofer IAO Institute, Wera developed a screwdriver handle designed to match the shape of the human hand as long ago as 1960s. After a long the development phase, the Wera Kraftform handle was launched to the market in 1968. It has been optimised through the years with new technologies, but has kept its proven shape. After all, the human hand has not changed either.



The hard materials used for the handle ensure rapid hand repositioning without any danger of the skin "sticking" to the handle. The surrounding hard zones with large diameters glide like wheels through the hand.

Large contact area



The large contact area - with particularly high friction to the soft zones - results in high torque transfer without any bruising from the edges.

Non-roll feature



The hexagonal non-roll feature prevents any rolling away at the workplace.

Identification marking



The screw symbol and tip size identification markings on the handle make it easier to find the right screwdriver in the tool case, or at the workplace.

Kraftform Plus – Series 300



Further versions in this product family:

				Ø	Å
mm	inch	mm	mm	mm	inch
5.0	-	90	98	7.2	3 35/64"
5.5	-	90	98	7.2	3 35/64"
6.0	-	90	98	7.2	3 35/64"
7.0	-	90	105	7.2	3 35/64"
8.0	-	90	105	9.3	3 35/64"
10.0	-	90	112	9.3	3 35/64"
13.0	-	90	112	11.0	3 35/64"
-	3/16"	90	98	7.2	3 35/64"
-	1/4"	90	98	7.2	3 35/64"
-	5/16"	90	105	9.3	3 35/64"
-	11/32"	90	105	9.3	3 35/64"
-	3/8"	90	112	9.3	3 35/64"
-	7/16"	90	112	11.0	3 35/64"
-	1/2"	90	112	11.0	3 35/64"
	5.0 5.5 6.0 7.0 8.0 10.0 13.0 - - - - - - - - - - - - -	5.0 - 5.5 - 6.0 - 7.0 - 8.0 - 10.0 - 13.0 - - 3/16" - 5/16" - 11/32" - 3/8" - 7/16"	mm inch mm 5.0 - 90 5.5 - 90 6.0 - 90 7.0 - 90 8.0 - 90 10.0 - 90 - 3/16" 90 - 1/4" 90 - 5/16" 90 - 11/32" 90 - 3/8" 90 - 7/16" 90	mm inch mm mm 5.0 - 90 98 5.5 - 90 98 6.0 - 90 98 7.0 - 90 105 8.0 - 90 105 10.0 - 90 112 13.0 - 90 98 - 3/16" 90 98 - 1/4" 90 98 - 5/16" 90 105 - 11/32" 90 105 - 3/8" 90 112 - 7/16" 90 112	mm inch mm mm mm 5.0 - 90 98 7.2 5.5 - 90 98 7.2 6.0 - 90 98 7.2 7.0 - 90 98 7.2 8.0 - 90 105 7.2 8.0 - 90 105 9.3 10.0 - 90 112 9.3 13.0 - 90 112 9.3 - 3/16" 90 98 7.2 - 1/4" 90 98 7.2 - 1/4" 90 98 7.2 - 1/4" 90 98 7.2 - 1/4" 90 98 7.2 - 1/4" 90 105 9.3 - 1/4" 90 105 9.3 - 11/32" 90 105 9.