



SPECIFICATION SHEET



Housing: Cast aluminum. Removable bar for variety of uses

Finish: BZ- Bronze

Lighting Integrated LED, 8 single cores, 2.5W, 160 Lumens, 3000 Kelvin, 120°
Source: beam spread, 8-18 volt AC operating votage. 25W Halogen equrivalent,

-4°F to +140°F ambient temperature.

Wiring: Fixture is prewired with a 10-ft 18-2 direct burial cord, pre-stripped for easy connection, wire connector sold seperately. Universal connector, silicone

filled wire nut or quick locking wire connector are available.

Mounting Bracket: Stainless steel glare shied, sppled with screws and anchor bolts. Break off

comers for easy installation.

Electrical Notes: A remote 12V magnetic transformer is required, can be ordered.

seperately Not for use with electronic tansformer. Increasing vollage above 12 volls may decrease the Ke of LED cores.

Dimensions:

Retaining walls. Patios, Gazebos, Decks, Benches, Stains, and Outdoors


Lving Spaces.

Dimensions:

13"(Length)x3"(Width)x0.91"(Height)

Warranty:

5 years warranty, with a rated life of 50,000 hours.



STB06

WWW.ABBALIGHTINGUSA.COM

E-mail: abbalightingusa@gmail.com

Tel: (818)835 9420

Fax: (800)360 2960