



2USB inCharge PRO 55 15W

General Information

| | |
|------|---|
| Name | inCharge PRO 55 EU F |
| SKU | 2U-449511, 2U-449535, 2U-449528, 2U-449542, 2U-449559 |

Basics

| | |
|--------------------------|---|
| Brand | 2USB |
| Model Number | 5503FBCX |
| EAN | 8718868449511, 8718868449535, 8718868449528, 8718868449542, 8718868449559 |
| Customs Number (HS-Code) | 8536.69.90.99 |
| Color | Glossy White, Glossy Cream, Matt White, Anthracite, Jet Black |

Dimensions

| | |
|---------------------|-----|
| Depth (mm) | 45 |
| Height (mm) | 71 |
| Width (mm) | 71 |
| Nett Weight (gram) | 92 |
| Gross Weight (gram) | 130 |
| Mounting Depth (mm) | 32 |

Technical Specifications

| | |
|---|--|
| Rated Voltage | 220-250V~ / 50Hz |
| Rated Current | 16A |
| Rated load | 3680W |
| Input Current | Max. 500mA |
| Input terminals | Screwless (push-in) terminals |
| Input wiring | 1,5 mm2 - 2x2,5mm2 rigid, rigid-stranded or flexible |
| Stripping Length (mm) | 11 |
| Output Ports | 1 x USB-A / 1 x USB-C |
| Output Voltage | 4,75 - 5,25VDC |
| Output Current | 0,01 - 3,0A (shared) |
| Energy Efficiency (%) | >82 |
| Stand-by Power (mW) | <80 |
| Socket Type | IEC Type F |
| Expected lifetime in hours at Full Load | 20.000 |
| Overvoltage Category (OVC) | III |
| Operating Temperature | 0-40°C |
| Storage Temperature | -20°C - 80°C |

Standards & Certifications

| | |
|-------------------------|--|
| Certifications | CB, KEMA-KEUR & VDE |
| CE Compliant | ✓ |
| EU Directives | RoHS Directive (2011/65/EU), EMC Directive (2014/30/EU), Low Voltage Directive (2014/35/EU), ErP Directive (2009/125/EC) |
| Socket-outlet Standards | NEK 502:2016, NEN 1020:2019, DIN VDE 0620-1:2021, SFS 5610:2004+A1:2008, UNE 20315-1-1:2009, SS 428 08 34:2013, NP 1620:1993 (Ed.2), UNE 20135-2-7:2008, IEC 60884-1:2010, ÖNORM E 8684-1:2010 |
| EMC & LVD Standards | EN 60669-2-1 (clause 26), EN 55032 (class B), EN 61000-3-2:2014, EN 61000-3-3:2013, EN 55024:2010, EN 55024-A1:2014, IEC-EN 61204-3:2018, IEC-EN 62368-1, IEC-EN 61558-1/-2-16 |