



2USB chargeUP TAE 12W 2,4A

General Information

Name	chargeUP TAE 12W 2,4A
SKU	2U-449474, 2U-449733

Basics

Brand	2USB
Model Number	JP-3502BD
EAN	8718868449474, 8718868449733
Customs Number (HS-Code)	8504.40.82.90
Color	Glossy White, Anthracite

Dimensions

Depth (mm)	43
Height (mm)	71
Width (mm)	71
Nett Weight (gram)	76
Gross Weight (gram)	108
Mounting Depth (mm)	32

Technical Specifications

Rated Voltage	100 - 250V~ 50/60Hz
Input Current	Max.1,5A
Input terminals	Screw terminals
Input wiring	0,75 mm ² - 2x2,5 mm ² rigid, rigid-stranded or flexible
Stripping Length (mm)	6
Output Ports	2 x USB-A
Output Voltage	4,75 - 5,25VDC
Output Current	0,01 - 2,4A (shared)
Energy Efficiency (%)	>85
Stand-by Power (mW)	<50
Expected lifetime in hours at Full Load	30.000
Overvoltage Category (OVC)	II
Operating Temperature	0-40°C
Storage Temperature	-20°C - 80°C

Standards & Certifications

Certifications	CB
CE Compliant	✓
EU Directives	RoHS Directive (2011/65/EU), EMC Directive (2014/30/eu), Low Voltage Directive (2014/35/EU), ErP Directive (2009/125/EC)
EMC & LVD Standards	EN 55032 (class B), EN 61000-3-2:2014, EN 61000-3-3:2013, EN 55024:2010, EN 55024-A1:2014, IEC-EN 60950-1