



FEATURES

- Designed to measure high capacity load for cranes, hoists, and winches
- Used with shackles to measure force
- Available in capacities ranging from 10,000 lbs to 250,000 lbs
- The display shows both kg and lb measurements
- Cost-effective solution for processing, monitoring, and controlling overhead loads
- Lightweight and compact design with high capacity
- Used with shackles to measure force
- Selectable weighing units: lb and kg
- Power: 110V-220V AC adapter, built-in rechargeable battery (up to 100 hrs)
- 26' load cell cable (longer options available)
- 5-year limited warranty

MODELS	CAPACITY
LS-927-10K	10,000 lb x 1 lb
LS-927-25K	25,000 lb x 10 lb
LS-927-50K	50,000 lb x 20 lb
LS-927-100K	100,000 lb x 50 lb
LS-927-200K	200,000 lb x 100 lb
LS-927-250K	250,000 lb x 100 lb

OPTIONAL ACCESSORIES

- Thermal printers
- Scoreboard (Large display)
- Data collection software
- Explosion proof upgrade
- Water-resistant upgrades
- Output systems (4-20ma or 0-5VRelay)
- Wireless (cordless connection)

HEAVY DUTY INDUSTRIAL TENSION LINK SCALE

RATED CAPACITY	DIMENSIONS					
	A	B	C	D	E	F
lb/inches						
10k lb	11.125	3.55	1.875	7.25	2.015	1.5
25k lb	11.125	3.55	1.875	7.25	2.015	1.5
50k lb	12.2	4.33	2.01	8.27	2.13	1.69
100k lb	16.5	5.0625	2.375	11.875	2.84	1.97
200k lb	23.625	7.09	3.875	15.75	4.6	3.15
250k lb	23.625	7.09	3.875	15.75	4.6	3.15
kg/mm						
4535.92 kg	282.575	90.17	47.625	184.15	51.181	38.1
11339.8 kg	282.575	90.17	47.625	184.15	51.181	38.1
22679.6 kg	309.88	109.982	51.054	210.058	54.102	42.926
45359.2 kg	419.1	128.5875	60.325	301.625	72.136	50.038
90718.4 kg	600.075	180.086	98.425	400.05	116.84	80.01
113398 kg	600.075	180.086	98.425	400.05	116.84	80.01

