



PRINTER SPECIFICATIONS:

- **Printing Method:** Direct Thermal Printing
- **Printing Speed:** Max. 100mm/s, 3.94" in/s
- **Resolution:** 8 dots/mm, 384 dots/line
- **Effective Printing Width:** 48mm, 1.89" in
- **Character Character Set:** GB2312, 16x16dots, or 24x24dots
- **Character:** 8x16dots, or 12x24dots, 9x17dots
- **Character per Line:** 32
- **Paper Spec Paper Type:** Thermal paper
- **Paper Width:** 57.5 ± 0.5mm, 2.26 ± 0.02" in
- **Paper Roll Diameter:** Max. 83.0mm, 3.27" in
- **Roll Core Inner Diameter:** 13mm(min.), 0.51" in(min.)
- **Paper Thickness:** 0.06 to 0.07mm, 0.0024" to 0.0027" in
- **Paper out detection:** Support
- **Paper Supply Method:** Drop-in Paper Load
- **Reliability MCBF:** 5 million lines
- **Printer Head Life:** >100km Printing length
- **Bar code type:** UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF, CODEBAR, CODE93, CODE128, QR CODE

PRINTER FEATURES:

- Long life, high speed, durable performance
- Low noise direct thermal printing
- Exquisite design and easy to use
- Function setup, auto-printing prompt
- **Emulation:** ESC/POS
- **Driver:** WIN2003/WINXP/WIN7/WIN8/WIN10
- **Drawer Port:** 1 Port
- **Interface:** U、US、S、P
- **Input Power:** 12V, 2A
- **Cash box control:** 12V, 24V
- **Net Weight:** 400g
- **Gross Weight:** 1.0kg
- **Printer Dimension (WxLxH):**
210mm(L)x135mm(W)x126mm(H)
8.27" in(L)x 5.31" in(W)x 4.96" in(H)
- **Application:** Restaurants, Department Stores, Kitchen, Convenience Stores, Specialty Retail, Super market.



Date: 05/01/2018
Time: 11:30:52
Net: 25.6 lb
Tare: 10.3 lb
Gross: 35.9 lb

PRINT OUT SAMPLE

COMPANY NAME
Date: 05/01/2018
Time: 11:30:52 pm
Gross Wt. (lbs): 35.9
Tare Wt. (lbs): 10.3
Net Wt. (lbs): 25.6

CUSTOM PRINT OUT SAMPLE

PRINTER FEATURES:

- Direct thermal sticker label printer
- Labels are 2.3" x 1.6", 800 labels per roll
- Easy to load thermal printer
- Paper clamps prevent jams
- Can use thermal roll paper, thermal label paper, and adhesive thermal paper
- Fast processing
- Print width: 3.1" (80mm)
- Paper diameter: Max 3.3" (85mm), Min 1" (25mm)
- Interface: USB + serial port
- Print Speed: 3-5 inches/s (120mm/s)
- Paper feeding method: Automatic
- Uses: Logistics print, single tag
- Duplex Printing: Yes
- Resolution 203dpi
- Memory: DRAM: 2M, FLSH:2M
- Power supply: 24DC, 2.0A
- Dimensions: 5.6" W x 8.5" L x 5.5" H
- Working Temp: 41 ~ 113°F, humidity: 10 ~ 80%





4 x 6 Labels

PRINTER FEATURES:

- Direct thermal sticker label printer
- Labels are 4" x 6", 800 labels per roll
- 203 dpi high resolution
- 2-8 inch/s high-speed printing
- 4.7" (120mm) paper exit chute
- Paper width Max. 118mm (4.64") Min. 20mm (0.78")
- Support two-dimensional bar-code printing (QR CODE)
- Three switchable pressures of print head
- Single-motor gear driven design and merged sensor design
- Separate mechanism structure, direct thermal printing
- Support Thermal paper, Thermal label, Adhesive thermal paper etc.
- Reserved external paper feeding chute; Easy paper feeding
- Optional external media holder supports 8.4"OD industrial-grade media rolls
- USB+ Serial interface
- Can take commands in ZPL (zebra printer language)
- Paper roll diameter is 5" (127mm)
- Dimensions: 7" x 7" x 9.4"

