



PRICE	
PART#	CAPACITY
LS-350-TM-20	20,000 lbs
LS-350-TM-25	25,000 lbs
LS-350-TM-30	30,000 lbs
LS-350-TM-40	40,000 lbs
LS-350-TM-50	50,000 lbs
LS-350-TM-100	100,000 lbs
LS-350-TM-200	200,000 lbs

RATED CAPACITY	DIMENSIONS										
	A	B	C	D	d	E	F	G	H	h	J
lb/inches											
20K - 25K lbs	4.00	10.00	8.00	0.78	0.78	8.00	7.50	6.00	0.75	0.75	6.00
30K - 40K lbs	4.00	14.00	10.00	0.78	0.78	8.00	11.50	7.50	1.00	0.75	6.00
50K - 100K lbs	7.00	14.00	10.00	1.12	1.12	9.00	11.50	7.50	1.00	1.00	6.50
200K lbs	8.00	25.00	16.00	1.63	1.63	12.00	20.00	11.00	1.50	1.50	8.00
kg/mm											
9,072-11,340 kg	101.60	254.00	203.20	19.81	19.81	203.20	190.50	152.40	19.05	19.05	152.40
13,608-18,144 kg	101.60	355.60	254.00	19.81	19.81	203.20	292.10	109.50	25.40	19.05	152.40
22,680-45,360 kg	177.80	355.60	254.00	28.45	28.45	228.60	292.10	190.50	25.40	25.40	165.10
90,720 kg	203.20	635.00	406.40	41.40	41.40	304.80	508.00	279.40	38.10	38.10	203.20

COMPLETE KIT INCLUDES:

- 3 or 4 LS-350 alloy steel load cells
- 3 or 4 LS-350-TM compression mounts
- 1 LS-416-SS stainless junction box

SPECIFICATIONS

- Rated Capacity:**
lbs: 20K/25K/30K/40K/50K/100K/200K
- Rated Output:**
 3.0mV/V
- Load Cell Resistance:**
 700 OHMS
- Load Cell Cable:**
 STANDARD
 10K - 40K lbs: 40ft/12m
 DOUBLE-SHIELDED
 50K - 200K lbs: 60ft/18m
- Safe Overload:**
 150% F.S
- Destructive Load:**
 300% F.S

- Excitation Recommended:**
 10-15V AC/DC
- Operation Temperature:**
 -20°C - 60°C (-4°F - 104°F)
- Construction:**
 Load Cell: Alloy Steel
 Module: Alloy Steel

