



PRICE	
PART#	CAPACITY
LS-730-SS-TM-0.25	250 lbs
LS-730-SS-TM-0.5	500 lbs
LS-730-SS-TM-1	1,000 lbs
LS-730-SS-TM-1.5	1,500 lbs
LS-730-SS-TM-2	2,000 lbs
LS-730-SS-TM-2.5	2,500 lbs
LS-730-SS-TM-4	4,000 lbs
LS-730-SS-TM-5	5,000 lbs
LS-730-SS-TM-5-LE	5,000 LE lbs
LS-730-SS-TM-10	10,000 lbs
LS-730-SS-TM-15	15,000 lbs
LS-730-SS-TM-20	20,000 lbs

RATED CAPACITY	DIMENSIONS								
	A	B	C	D	E	F	G	H	I
lb/inches									
250 - 5K lbs	7.12	4.00-4.50	5.00	0.56	2.00	4.00	0.70	4.00	0.63
5K LE - 10K lbs	8.50	5.00-5.50	5.00	0.75	3.00	4.00	0.94	5.00	0.63
15K - 20K lbs	10.88	7.00-7.50	6.00	0.87	4.63	4.50	1.44	6.88	0.88
kg/mm									
113-2,268 kg	180.85	101.60-114.30	127.00	14.22	50.80	101.60	17.78	101.60	16.00
2,268 LE-4,536 kg	215.90	127.00-139.70	127.00	19.05	76.20	101.60	23.88	127.00	16.00
6,804-9,072 kg	276.35	177.80-190.50	152.40	22.10	117.60	114.30	36.58	174.75	22.35

COMPLETE KIT INCLUDES:

- 3 or 4 LS-730 NTEP certified alloy steel load cells
- 3 or 4 LS-730-TM compression mounts
- 1 LS-416-SS stainless junction box

SPECIFICATIONS

Rated Capacity:	Safe Overload:
lbs: 250/500/1K/1.5K/2K/2.5K/ 4K/5K/5K LE/10K/15K/20K	150% F.S
Rated Output:	Destructive Load:
3.0mV/V	300% F.S
Load Cell Resistance:	Excitation Recommended:
350 OHMS	10-15V AC/DC
Load Cell Cable:	Operation Temperature:
Standard Cable: 250 - 5K lbs: 20ft/6m 10K - 20K lbs: 40ft/12m	-10°C - 40°C (14°F - 104°F)
	Construction:
	Load Cell: Stainless Steel Module: Stainless Steel

