



## Basic features

Approval/Conformity	cULus CE UKCA WEEE
Basic standard	IEC 60947-5-2

## Display/Operation

Function indicator	yes
Power indicator	no

## Electrical connection

Connection	M12x1-Male, 4-pin, A-coded
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

## Electrical data

Load capacitance max. at Ue	1 $\mu$ F
Magnetic field strength, interference field	100 kA/m
Min. operating current I <sub>m</sub>	0 mA
No-load current I <sub>o</sub> max., damped	10 mA
No-load current I <sub>o</sub> max., undamped	2 mA
Operating voltage U <sub>b</sub>	10...30 VDC
Output resistance R <sub>a</sub>	33.0 k $\Omega$ m + D
Protection class	II
Rated insulation voltage U <sub>i</sub>	250 V AC
Rated operating current I <sub>e</sub>	200 mA
Rated operating voltage U <sub>e</sub> DC	24 V
Rated short circuit current	100 A
Ready delay t <sub>v</sub> max.	20 ms
Residual current I <sub>r</sub> max.	80 $\mu$ A
Ripple max. (% of U <sub>e</sub> )	10 %
Switching frequency	200 Hz
Utilization category	DC -13
Voltage drop static max.	1.5 V

## Environmental conditions

Ambient temperature	-25...70 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 g <sub>n</sub> , 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP67
Magnetic field immune	magnetic field immune (AC/DC)

## Functional safety

MTTF (40 °C)	775 a
--------------	-------

## Interface

Switching output PNP normally open (NO)

## Material

Housing material Brass, PTFE coated  
 Material sensing surface PTFE

## Mechanical data

Dimension  $\varnothing 18 \times 65$  mm  
 Installation for flush mounting  
 Mounting length 40.00 mm  
 Size M18x1  
 Tightening torque 12 Nm

## Range/Distance

Assured operating distance  $S_a$  4 mm  
 Hysteresis H max. (% of  $S_r$ ) 15.0 %  
 Rated operating distance  $S_n$  5 mm  
 Real switching distance  $s_r$  5 mm  
 Repeat accuracy max. (% of  $S_r$ ) 5.0 %  
 Temperature drift max. (% of  $S_r$ ) 10 %  
 Tolerance  $S_r$   $\pm 10$  %

## Remarks

The sensor is functional again after the overload has been eliminated.  
 For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

## Connector Drawings



## Wiring Diagrams

