



1) Sensing surface, 2) Tightening torque, 3) see R/W head table



**Basic features**

Antenna type	round
Approval/Conformity	CE UKCA Ecolab WEEE
EN 55011	Size 1, Cl. A
EN 55022	Size 1, Cl. B
Principle of operation	Data carrier

**Electrical data**

Data retention time/years	≥ 10
Memory organization	28 × 4 bits
Programming cycles	up to 70 °C: 100,000
Programming time	for 16 bytes: 0.1 s
Read cycles	Unlimited
Read time	for 16 bytes: 0.03 s User ID for 8 bytes: 0.02 s

**Environmental conditions**

Ambient temperature	-40...85 °C
Continuous shock load	yes
EN 60068-2-27, Shock	yes
EN 60068-2-32 Free fall	yes
EN 60068-2-6, Vibration	yes
IP rating	IP68
IP rating per DIN 40050	IPx9K
Storage temperature temporary	-40...220 °C 1x1000 h, 1500x30 min

**Functional Characteristics**

Memory type	EEPROM
Supported data carrier types	DIN ISO 15693
UID serial number, read-only	8 Byte
User data, read/write	112 Byte

**Material**

Housing material	PPS
------------------	-----

**Mechanical data**

Application weight	32.00 g
Dimension	51.5 × 6.4 × 51.5 mm
Installation	metal-free (clear zone)

HF (13.56 MHz)  
BIS M-135-03/L-HT  
Order Code: BIS00Y4

**BALLUFF**

#### Remarks

---

For installation in metal: Observe clear zone.  
Time specification includes data check.  
For installation requirements see corresponding read/write head.  
Only when used together with the appropriate read/write head.  
Values are under rated conditions unless otherwise specified.  
The data carrier meets the device protection level EPL Gb and can therefore be used n Zone 1 with Gas Group II. A and II. B.  
Storage temperature 1000 h or 1500 cycles à 30 min.